



Report No. 5423

IMP Performance Measurements Preliminary Results

John G. Zornig

October 1983

Prepared for:
Maryland Procurement Office

BBN Communications

Report No. 5423

IMP Performance Measurements Preliminary Results

John G. Zornig

October 1983

This report has been prepared for the Maryland Procurement Office, Fort Meade, Maryland under the provisions of Contract MDA904-83-C-0959, Job Order 83-001.

1. INTRODUCTION

This is the final report provided under the provisions of Job Order 83-001 of Maryland Procurement Office Contract MDA-83-C-0959. It reports the current status of an investigation of the performance properties of the BNCC C/30 Interface Message Processor (IMP). This investigation is incomplete and therefore this report will be as succinct as possible. The results of the study will be reported in more detail when it is complete and the author is in a position to make recommendations.

2. BASELINE MEASUREMENTS

During the period of the Job Order a three part measurement experiment was designed and conducted on a trial basis. The experiment consisted of simultaneous collection of frequency of occurrence data on C/30 NMFS microcode instructions and 4320 process execution together with BBN CUMSTATS traffic measurements as a normalization. It was expected that these data would reveal that a large portion of the MBB processor bandwidth was being used for input/output, indicating a potential for improvement by implementation of more efficient I/O hardware and firmware.

For these measurements, two systems had to be designed and implemented. These were (1) an automated system for collection and analysis of logic analyser records of micro-program counter activity, and (2) a process timing system for measurement of

macrocode process activity. Both systems were built, tested, and used to collect the data enclosed with this report.

Time constraints have not permitted detailed analysis of the results of this experiment. However, preliminary inspection of the data have indicated that:

- a. There is no reason based on the data to believe that more than 20% of the processor bandwidth is used for I/O under even heavy load conditions.
- b. A minimum of about 10% of the processor bandwidth is used for I/O, presumably synchronous idling, under no load conditions.
- c. The relationship between traffic and I/O process activity is linear in both trunk and host interface cases. The slope is, however, different. Trunk load is about 0.2%/packet/sec. not including RFNMS, and host interface load is about 0.3%/packet/sec.
- d. An appreciable amount of overhead (2-5%) involving spurious console I/O polling is present but would be avoidable with suitable microcode modification.
- e. The current instrumentation does not reveal fraction of time spent idling in the macrocode background process.

3. ATTACHMENT OF 256kb TRUNKS

An attempt was made to find obstacles to connection of 256kb synchronous trunks to the current 4320 NMFS IMP. Microcode observations have revealed that there exist uninterruptable strips of instruction execution long enough to disturb such operation. Preliminary analyses of these observations indicates that these strips may be avoidable and that 256kb connection may therefore be possible. Modification and testing of the NMFS code would be necessary in order to verify this hypothesis.

3. INCREASE OF AGGREGATE THROUGHPUT

No determination of the feasibility of attaching a total of 3-256 kb trunks and 2-256kb hosts can be made until the physical attachment problem is solved and the excess processor capacity is determined. Based on the assumption that physical modification of the IMP would be necessary in order to handle the increase in load, a study of the feasibility of a number of alternatives was initiated. This study has resulted in the identification of a number of alternatives, but no firm analysis of cost and effectiveness has been made.

APPENDIX A: Measured Microengine Profiles

The following profiles were taken during a 12 hour period as indicated. They display the fraction of real time that the micro-program counter was observed to be in each part of the NMFS program, and a summary of that data by class of activity. Each measurement report is followed by the CUMSTATS report of IMP activity during the period of the measurement. These measurements are preliminary and should not be considered to be confirmed or reliable.

EXPERIMENT DURATION

FROM SEP 28, 1983 12:01:24.000 BBN-NMC TIME
 TO SEP 28, 1983 12:57:17.000 BBN-NMC TIME

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

33 CUM STAT'S (100% OF MAX.)
 TIME COVERED BY DATA = 3460.301 SECONDS

C30 IMP (EXA)

MESSAGE AND PACKET SIZE STATISTICS

HISTOGRAM OF MESSAGE LENGTH				LOG2 HISTOGRAM OF PACKET LENGTH			
PACKETS	FROM HOSTS	INTO HOSTS	16-BIT	HOSTS		CHAN	
			DATA	FROM	INTO	OUT	
1	95050	74085	WORDS				
2	1506	944	0-1	12	3	971	
3	216	143	2-3	32	27	73103	
4	10	50	4-7	151	216	1391	
5	439	651	8-15	8922	8452	9763	
6	4	5	16-31	81698	48736	77203	
7	194	11	32-63	12776	22730	14041	
8	158	25					
TOTALS	97577	75914		103591	80164	176472	
MEAN/SEC (MSG)	28.20	21.94	(PKTS)	29.94	23.17	51.00	
MEAN BITS/SEC	11897.42	10976.38					
MEAN PKTS/MSG	1.06	1.06					
MEAN BITS/MSG	421.91	500.32					
MEAN BITS/PKT	397.42	473.80					

H2I: PKTS/SEC= 29.9 MSGS/SEC= 28.2
 I2H: PKTS/SEC= 23.2 MSGS/SEC= 21.9 PKTS & RFNMS = 51.4
 M2I: PKTS/SEC= 50.5
 I2M: PKTS/SEC= 51.0
 TSK: PKTS/SEC= 102.4

HOST MSG TOTALS	CSNET	BBN-N	DIV6-	FIBER
	-CIC	OC	TAC	-GW
TOTAL FROM	12551	2776	14836	67414
CONTROL TO	12551	2776	14836	67414

FAKE HOST MSG TOTALS	TTY	DEBUG	PC/TR	DS/ST
TOTAL FROM	0	0	0	0
CONTROL TO	0	0	0	0

CHANNEL ACTIVITY

NEIGHBOR	PKTS OUT	BITS OUT	BITS/SEC
UCC4	75258	1.71E+07	4950.30
UCC8	48756	1.28E+07	3685.86
UCC2	52458	1.16E+07	3345.71
TOTAL	176472	4.15E+07	11981.87
MEAN (DATA ONLY) BITS/PKT OUT CHANNELS =			234.94

# OF ROUND-TRIPS & MEAN RT TIME, TO FOLLOWING IMPS /SITE				#TRIPS, #MSEC/
UCC2	17555,	46 /	UCC4	19325, 98 / DB5 1, 90
UCC6	3930,	76 /	UCC7	487, 91 / UCC8 23586, 63
NCLB9	1155,	127 /	MLB10	10381, 81 / UCC14 21271, 46
TEST5	2,	102 /		

97693 ROUND-TRIPS TO ALL DESTINATIONS

TOTAL MEAN ROUND-TRIP DELAY = 66.42 MSEC.

TOTAL ROUTING UPDATES TRANSMITTED PER SECOND = 1.01
PER LINE:

TO UCC4	0.34	(60.70 BITS)	PER SECOND
TO UCC8	0.34	(60.79 BITS)	PER SECOND
TO UCC2	0.34	(60.79 BITS)	PER SECOND

AVERAGE NEIGHBORS IN ROUTING UPDATE = 2.74

TOTAL NULLS PER SECOND (ALL LINES) = 44.64
PER LINE:

TO UCC4	15.94	(2422.48 BITS)	PER SECOND
TO UCC8	16.14	(2453.75 BITS)	PER SECOND
TO UCC2	12.56	(1909.24 BITS)	PER SECOND

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

EXPERIMENT DURATION

FROM SEP 28, 1983 13:00:50.000 BBN-NMC TIME
 TO SEP 28, 1983 13:56:45.000 BBN-NMC TIME

--14---UCC14----14---UCC14----14---UCC14----14---UCC14----14---UCC14----

33 CUM STAT'S (100% OF MAX.)
 TIME COVERED BY DATA = 3460.301 SECONDS

C30 IMP (EXA)

MESSAGE AND PACKET SIZE STATISTICS

HISTOGRAM OF MESSAGE LENGTH			LOG2 HISTOGRAM OF PACKET LENGTH			
PACKETS	FROM HOSTS	INTO HOSTS	16-BIT DATA WORDS	HOSTS		CHAN OUT
				FROM	INTO	
1	100899	80686	0-1	19	17	1071
2	1432	1111	2-3	34	28	79470
3	377	201	4-7	160	188	1526
4	259	80	8-15	9570	9321	10109
5	317	377	16-31	87097	55905	80525
6	14	7	32-63	11501	21204	15773
7	34	31				
8	68	86				

TOTALS	103400	82579		108381	86663	188474
MEAN/SEC (MSG)	29.88	23.86	(PKTS)	31.32	25.04	54.47
MEAN BITS/SEC	12214.66	11557.25				
MEAN PKTS/MSG	1.05	1.05				
MEAN BITS/MSG	408.77	484.28				
MEAN BITS/PKT	389.98	461.46				

H2I: PKTS/SEC= 31.3 MSGS/SEC= 29.9
 I2H: PKTS/SEC= 25.0 MSGS/SEC= 23.9 PKTS & RFNMS = 54.9
 M2I: PKTS/SEC= 54.2
 I2M: PKTS/SEC= 54.5
 TSK: PKTS/SEC= 109.4

HOST MSG TOTALS	CSNET	BBN-N	DIV6-	FIBER
	-CIC	OC	TAC	-GW
TOTAL FROM	11275	6453	16404	69268
CONTROL TO	11275	6453	16404	69268

FAKE HOST MSG TOTALS	TTY	DEBUG	PC/TR	DS/ST
TOTAL FROM	0	0	0	0
CONTROL TO	0	0	0	0

CHANNEL ACTIVITY

NEIGHBOR	PKTS OUT	BITS OUT	BITS/SEC
UCC4	60056	1.35E+07	3901.77
UCC8	75821	1.87E+07	5407.50
UCC2	52597	1.20E+07	3461.04
TOTAL	188474	4.42E+07	12770.21
MEAN (DATA ONLY) BITS/PKT OUT CHANNELS =			234.46

# OF ROUND-TRIPS & MEAN RT TIME,	TO FOLLOWING IMPS /SITE	#TRIPS, #MSEC/
UCC2 16670 64 /	UCC4 15329, 101 /	DB5 878, 146
UCC6 6253, 112 /	UCC7 2030, 130 /	UCC8 34395, 118
NCLB9 2620, 135 /	MLB10 2118, 109 /	UCC14 23224, 70
TEST5 1, 96 /		

103518 ROUND-TRIPS TO ALL DESTINATIONS

TOTAL MEAN ROUND-TRIP DELAY = 96.41 MSEC.

TOTAL ROUTING UPDATES TRANSMITTED PER SECOND = 1.09
PER LINE:

TO UCC4	0.36	(65.99 BITS)	PER SECOND
TO UCC8	0.36	(65.99 BITS)	PER SECOND
TO UCC2	0.36	(65.99 BITS)	PER SECOND

AVERAGE NEIGHBORS IN ROUTING UPDATE = 2.83

TOTAL NULLS PER SECOND (ALL LINES) = 47.02
PER LINE:

TO UCC4	14.11	(2144.33 BITS)	PER SECOND
TO UCC8	19.82	(3012.55 BITS)	PER SECOND
TO UCC2	13.10	(1990.50 BITS)	PER SECOND

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14--

EXPERIMENT DURATION

FROM SEP 28, 1983 14:00:17.000 BBN-NMC TIME
 TO SEP 28, 1983 14:58:05.000 BBN-NMC TIME

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

34 CUM STAT'S (100% OF MAX.)
 TIME COVERED BY DATA = 3565.158 SECONDS

C30 IMP (EXA)

MESSAGE AND PACKET SIZE STATISTICS

HISTOGRAM OF MESSAGE LENGTH			LOG2 HISTOGRAM OF PACKET LENGTH			
PACKETS	FROM HOSTS	INTO HOSTS	16-BIT DATA WORDS	HOSTS		CHAN
				FROM	INTO	OUT
1	138597	96580	0-1	32	41	2389
2	2310	2175	2-3	82	50	111659
3	106	529	4-7	174	658	3258
4	9	152	8-15	11052	11160	12596
5	20	1037	16-31	123080	67648	124311
6	0	58	32-63	9251	30458	22108
7	0	27				
8	0	146				
TOTALS	141042	100704		143671	110015	276321
MEAN/SEC (MSG)	30.56	28.25	(PKTS)	40.30	30.86	77.51
MEAN BITS/SEC	14807.70	14895.31				
MEAN PKTS/MSG	1.02	1.09				
MEAN BITS/MSG	374.30	527.33				
MEAN BITS/PKT	367.45	482.70				

H2I: PKTS/SEC= 40.3 MSGS/SEC= 39.6
 I2H: PKTS/SEC= 30.9 MSGS/SEC= 28.2 PKTS & RFNMS = 70.4
 M2I: PKTS/SEC= 79.4
 I2M: PKTS/SEC= 77.5
 TSK: PKTS/SEC= 147.9

HOST MSG TOTALS	CSNET	BBN-N	DIV6-	FIBER
	-CIC	OC	TAC	-GW
TOTAL FROM	13307	3349	19127	105262
CONTROL TO	13307	3349	19127	105265

FAKE HOST MSG TOTALS	TTY	DEBUG	PC/TR	DS/ST
TOTAL FROM	0	0	0	0
CONTROL TO	0	0	0	0

CHANNEL ACTIVITY			
NEIGHBOR	PKTS OUT	BITS OUT	BITS/SEC
UCC4	80210	1.70E+07	4776.43
UCC8	93479	2.21E+07	6202.99
UCC2	102632	2.79E+07	7833.36
TOTAL	276321	6.71E+07	18812.79
MEAN (DATA ONLY) BITS/PKT OUT CHANNELS =			242.73

# OF ROUND-TRIPS & MEAN RT TIME, TO FOLLOWING IMPS /SITE	#TRIPS, #MSEC/
UCC2 40975, 135 / UCC4 18033, 190 / DB5	49, 94
UCC6 10231, 149 / UCC7 978. 241 / UCC8	35588, 115
NCLB9 2110, 309 / MLB10 5729, 242 / UCC14	27478, 146

141171 ROUND-TRIPS TO ALL DESTINATIONS

TOTAL MEAN ROUND-TRIP DELAY = 147.84 MSEC.

TOTAL ROUTING UPDATES TRANSMITTED PER SECOND = 1.36

PER LINE:

TO UCC4	0.45	(82.71 BITS)	PER SECOND
TO UCC8	0.45	(82.71 BITS)	PER SECOND
TO UCC2	0.45	(82.71 BITS)	PER SECOND

AVERAGE NEIGHBORS IN ROUTING UPDATE = 2.93

TOTAL NULLS PER SECOND (ALL LINES) = 63.03

PER LINE:

TO UCC4	18.21	(2768.15 BITS)	PER SECOND
TO UCC8	21.84	(3319.29 BITS)	PER SECOND
TO UCC2	22.98	(3492.95 BITS)	PER SECOND

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

EXPERIMENT DURATION
 FROM SEP 28, 1983 15:01:34.000 BBN-NMC TIME
 TO SEP 28, 1983 15:57:33.000 BBN-NMC TIME

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

33 CUM STAT'S (100% OF MAX.)
 TIME COVERED BY DATA = 3460.301 SECONDS

C30 IMP (EXA)

MESSAGE AND PACKET SIZE STATISTICS				LOG2 HISTOGRAM OF PACKET LENGTH			
HISTOGRAM OF MESSAGE LENGTH		HOSTS		HOSTS		CHAN	
PACKETS	FROM	INTO	HOSTS	FROM	INTO	OUT	OUT
1	124325	82821	16-BIT				
2	2027	2840	DATA				
3	103	462	WORDS				
4	7	27	0-1	10	9	986	
5	20	179	2-3	17	17	78194	
6	13	3	4-7	101	817	1504	
7	10	2	8-15	10295	9871	10512	
8	20	10	16-31	108242	56170	98386	
			32-63	10459	24118	9470	
TOTALS	126525	86344		129124	91002	199052	
MEAN/SEC (MSG)	36.56	24.95	(PKTS)	37.32	26.30	57.52	
MEAN BITS/SEC	13884.17	12160.01					
MEAN PKTS/MSG	1.02	1.05					
MEAN BITS/MSG	379.71	487.32					
MEAN BITS/PKT	372.07	462.38					

H2T: PKTS/SEC= 37.3 MSGS/SEC= 36.6
 I2H: PKTS/SEC= 26.3 MSGS/SEC= 25.0 PKTS & RFNMS = 62.9
 M2I: PKTS/SEC= 58.1
 I2M: PKTS/SEC= 57.5
 TSK: PKTS/SEC= 120.4

HOST MSG TOTALS	CSNET	BBN-N	DIV6-	FIBER
	-CIC	OC	TAC	-GW
TOTAL FROM	13571	4385	23197	85372
CONTROL TO	13571	4385	23198	85372

FAKE HOST MSG TOTALS	TTY	DEBUG	PC/TR	DS/ST
TOTAL FROM	0	0	0	0
CONTROL TO	0	0	0	0

CHANNEL ACTIVITY			
NEIGHBOR	PKTS OUT	BITS OUT	BITS/SEC
UCC4	67058	1.39E+07	4005.21
UCC8	73725	1.89E+07	5449.09
UCC2	58269	1.20E+07	3470.53
TOTAL	199052	4.47E+07	12924.83
MEAN (DATA ONLY)	BITS/PKT OUT CHANNELS = 224.68		

# OF ROUND-TRIPS & MEAN RT TIME, TO FOLLOWING IMPS /SITE #TRIPS, #MSEC/										
UCC2	22466,	44	/	UCC4	18252,	90	/	DB5	3,	100
UCC6	7207,	75	/	UCC7	80,	80	/	UCC8	42917.	75
NCLB9	3034,	107	/	MLB10	5561,	99	/	UCC14	27117,	80
TEST5	2,	115	/							

126639 ROUND-TRIPS TO ALL DESTINATIONS

TOTAL MEAN ROUND-TRIP DELAY = 74.54 MSEC.

TOTAL ROUTING UPDATES TRANSMITTED PER SECOND = 0.86

PER LINE:

TO	UCC4	0.29	(51.78	BITS)	PER	SECOND
TO	UCC8	0.29	(51.78	BITS)	PER	SECOND
TO	UCC2	0.29	(51.78	BITS)	PER	SECOND

AVERAGE NEIGHBORS IN ROUTING UPDATE = 2.7"

TOTAL NULLS PER SECOND (ALL LINES) = 51.71

PER LINE:

TO	UCC4	15.86	(2411.45	BITS)	PER	SECOND
TO	UCC8	21.68	(3295.61	BITS)	PER	SECOND
TO	UCC2	14.16	(2152.41	BITS)	PER	SECOND

--14---UCC14----14---UCC14----14---UCC14----14---UCC14----14---UCC14----

EXPERIMENT DURATION

FROM SEP 28, 1983 16:01:02.000 BBN-NMC TIME
 TO SEP 28, 1983 16:58:46.000 BBN-NMC TIME

--14---UCC14----14---UCC14----14---UCC14----14---UCC14----14---UCC14----14---UCC14---

34 CUM STAT'S (100% OF MAX.)
 TIME COVERED BY DATA = 3565.158 SECONDS

C30 IMP (EXA)

MESSAGE AND PACKET SIZE STATISTICS				LOG2 HISTOGRAM OF PACKET LENGTH			
HISTOGRAM OF MESSAGE LENGTH		HOSTS		HOSTS		HOSTS	
PACKETS	FROM	INTO	HOSTS	16-BIT DATA WORDS	FROM	INTO	CHAN OUT
1	114536	72908		0-1	14	20	763
2	1125	4039		2-3	13	18	78552
3	8	623		4-7	182	1367	1238
4	2	26		8-15	9936	9938	10009
5	2	528		16-31	101527	45758	96704
6	0	0		32-63	5156	28514	10934
7	0	0					
8	0	2					

TOTALS	115673	78126			116828	85615	198200
MEAN/SEC (MSG)	32.45	21.91		(PKTS)	32.77	24.01	55.59
MEAN BITS/SEC	11626.10	11956.41					
MEAN PKTS/MSG	1.01	1.10					
MEAN BITS/MSG	358.33	545.61					
MEAN BITS/PKT	354.79	497.89					

H2I:	PKTS/SEC=	32.8	MSGS/SEC=	32.4		
I2H:	PKTS/SEC=	24.0	MSGS/SEC=	21.9	PKTS & RFNMS =	56.5
M2I:	PKTS/SEC=	57.4				
I2M:	PKTS/SEC=	55.6				
TSK:	PKTS/SEC=	112.1				

HOST MSG TOTALS	CSNET	BBN-N	DIV6-	FIBER
	-CIC	OC	TAC	-GW
TOTAL FROM	8750	2557	24630	79735
CONTROL TO	8750	2557	24632	79734

FAKE HOST MSG TOTALS	TTY	DEBUG	PC/TR	DS/ST
TOTAL FROM	0	0	0	0
CONTROL TO	0	0	0	0

CHANNEL ACTIVITY			
NEIGHBOR	PKTS OUT	BITS OUT	BITS/SEC
UCC4	74994	1.60E+07	4493.03
UCC8	62883	1.60E+07	4478.66
UCC2	60323	1.36E+07	3809.66
TOTAL	198200	4.56E+07	12781.35
MEAN (DATA ONLY) BITS/PKT OUT CHANNELS =			229.91

# OF ROUND-TRIPS & MEAN RT TIME, TO FOLLOWING IMPS /SITE #TRIPS, #MSEC/									
UCC2	20961,	45	/	UCC4	23498,	83	/	DB5	1, 96
UCC6	10914,	79	/	UCC7	697,	75	/	UCC8	34622, 53
NCLB9	1382,	128	/	MLB10	3297,	93	/	UCC14	20418, 45

115790 ROUND-TRIPS TO ALL DESTINATIONS

TOTAL MEAN ROUND-TRIP DELAY = 60.91 MSEC.

TOTAL ROUTING UPDATES TRANSMITTED PER SECOND = 0.96
PER LINE:

TO	UCC4	0.32	(57.75	BITS)	PER	SECOND
TO	UCC8	0.32	(57.75	BITS)	PER	SECOND
TO	UCC2	0.32	(57.75	BITS)	PER	SECOND

AVERAGE NEIGHBORS IN ROUTING UPDATE = 2.82

TOTAL NULLS PER SECOND (ALL LINES) = 51.12
PER LINE:

TO	UCC4	16.01	(2433.04	BITS)	PER	SECOND
TO	UCC8	20.20	(3070.82	BITS)	PER	SECOND
TO	UCC2	14.91	(2265.74	BITS)	PER	SECOND

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

EXPERIMENT DURATION

FROM SEP 28, 1983 19:01:04.000 BBN-NMC TIME
 TO SEP 28, 1983 19:56:58.000 BBN-NMC TIME

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

33 CUM STAT'S (100% OF MAX.)
 TIME COVERED BY DATA = 3460.301 SECONDS

C30 IMP (EXA)

MESSAGE AND PACKET SIZE STATISTICS

HISTOGRAM OF MESSAGE LENGTH				LOG2 HISTOGRAM OF PACKET LENGTH			
PACKETS	FROM	HOSTS INTO	HOSTS	16-BIT	HOSTS	HOSTS	CHAN
				DATA	FROM	INTO	OUT
1	29738		24994	WORDS			
2	219		186	0-1	1	2	756
3	16		13	2-3	12	3	32570
4	0		2	4-7	20	61	990
5	3		2	8-15	4747	4696	6667
6	66		0	16-31	22505	14653	25193
7	42		0	32-63	3660	6008	12019
8	2		0				

TOTALS	30086		25197		30945	25423	78195
MEAN/SEC (MSG)	8.69		7.28	(PKTS)	8.94	7.35	22.60
MEAN BITS/SEC	3510.71		3205.75				
MEAN PKTS/MSG	1.03		1.01				
MEAN BITS/MSG	403.78		440.25				
MEAN BITS/PKT	392.57		436.33				

H2I: PKTS/SEC= 8.9 MSGS/SEC= 8.7
 I2H: PKTS/SEC= 7.3 MSGS/SEC= 7.3 PKTS & RFNMS = 16.0
 M2I: PKTS/SEC= 22.4
 I2M: PKTS/SEC= 22.6
 TSK: PKTS/SEC= 38.6

HOST MSG TOTALS	CSNET	BBN-N	DIV6-	FIBER
	-CIC	OC	TAC	-GW
TOTAL FROM	5205	628	635	23618
CONTROL TO	5205	628	635	23618

FAKE HOST MSG TOTALS	TTY	DEBUG	PC/TR	DS/ST
TOTAL FROM	0	0	0	0
CONTROL TO	0	0	0	0

CHANNEL ACTIVITY

NEIGHBOR	PKTS OUT	BITS OUT	BITS/SEC
UCC4	28301	7.03E+06	2031.53
UCC8	28985	1.06E+07	3065.18
UCC2	20909	4.09E+06	1181.86
TOTAL	78195	2.17E+07	6278.57
MEAN (DATA ONLY) BITS/PKT OUT CHANNELS =			277.84

# OF ROUND-TRIPS & MEAN RT TIME, TO FOLLOWING IMPS /SITE #TRIPS, #MSEC/								
UCC2	4840,	39 /	UCC4	6381,	48 /	UCC6	1297,	96
UCC7	2096,	61 /	UCC8	12717.	79 /	MLB10	1668,	63
UCC14	1332,	12 /						

30331 ROUND-TRIPS TO ALL DESTINATIONS

TOTAL MEAN ROUND-TRIP DELAY = 61.48 MSEC.

TOTAL ROUTING UPDATES TRANSMITTED PER SECOND = 1.01

PER LINE:

TO UCC4	0.34	(60.75	BITS)	PER SECOND
TO UCC8	0.34	(60.75	BITS)	PER SECOND
TO UCC2	0.34	(60.75	BITS)	PER SECOND

AVERAGE NEIGHBORS IN ROUTING UPDATE = 2.80

TOTAL NULLS PER SECOND (ALL LINES) = 20.03

PER LINE:

TO UCC4	7.28	(1106.17	BITS)	PER SECOND
TO UCC8	7.22	(1097.42	BITS)	PER SECOND
TO UCC2	5.54	(841.55	BITS)	PER SECOND

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

EXPERIMENT DURATION

FROM SEP 28, 1983 20:00:27.000 BBN-NMC TIME
 TO SEP 28, 1983 20:59:52.000 BBN-NMC TIME

--14---UCC14----14---UCC14----14---UCC14----14---UCC14----14---UCC14----

35 CUM STAT'S (100% OF MAX.)
 TIME COVERED BY DATA = 3670.016 SECONDS

C30 IMP (EXA)

MESSAGE AND PACKET SIZE STATISTICS

HISTOGRAM OF MESSAGE LENGTH				LOG2 HISTOGRAM OF PACKET LENGTH			
PACKETS	FROM HOSTS	INTO HOSTS	16-BIT DATA	FROM HOSTS	INTO HOSTS	CHAN OUT	
1	20535	17860	WORDS				
2	327	91	0-1	0	0	385	
3	44	15	2-3	17	1	20477	
4	0	2	4-7	39	21	502	
5	2	0	8-15	4615	4606	6317	
6	0	0	16-31	15246	11784	15473	
7	0	1	32-63	1414	1706	3545	
8	0	2					
TOTALS	20908	17971	(PKTS)	21331	18118	46699	
MEAN/SEC (MSG)	5.70	4.90		5.81	4.94	12.72	
MEAN BITS/SEC	2058.50	1788.47					
MEAN PKTS/MSG	1.02	1.01					
MEAN BITS/MSG	361.33	365.24					
MEAN BITS/PKT	354.17	362.27					

H2I: PKTS/SEC= 5.8 MSGS/SEC= 5.7
 I2H: PKTS/SEC= 4.9 MSGS/SEC= 4.9 PKTS & RFNMS = 10.6
 M2I: PKTS/SEC= 12.6
 I2M: PKTS/SEC= 12.7
 TSK: PKTS/SEC= 23.4

HOST MSG TOTALS	CSNET	BBN-N	DIV6-	FIBER
	-CIC	OC	TAC	-GW
TOTAL FROM	2717	230	3114	14847
CONTROL TO	2717	230	3114	14847

FAKE HOST MSG TOTALS	TTY	DEBUG	PC/TR	DS/ST
TOTAL FROM	0	0	0	0
CONTROL TO	0	0	0	0

CHANNEL ACTIVITY			
NEIGHBOR	PKTS OUT	BITS OUT	BITS/SEC
UCC4	19315	3.49E+06	951.56
UCC8	18679	4.84E+06	1319.32
UCC2	8705	1.69E+06	460.73
TOTAL	46699	1.00E+07	2731.61
MEAN (DATA ONLY) BITS/PKT OUT CHANNELS =			214.67

# OF ROUND-TRIPS & MEAN RT TIME, TO FOLLOWING IMPS /SITE #TRIPS, #MSEC/										
UCC4	3146,	33	/	UCC6	3235,	57	/	UCC7	2275,	53
UCC8	7415,	33	/	MLB10	3289,	57	/	UCC14	1671,	8

21031 ROUND-TRIPS TO ALL DESTINATIONS

TOTAL MEAN ROUND-TRIP DELAY = 40.42 MSEC.

TOTAL ROUTING UPDATES TRANSMITTED PER SECOND = 0.84

PER LINE:

TO	UCC4	0.28	(50.49	BITS)	PER	SECOND
TO	UCC8	0.28	(50.49	BITS)	PER	SECOND
TO	UCC2	0.28	(50.49	BITS)	PER	SECOND

AVERAGE NEIGHBORS IN ROUTING UPDATE = 2.72

TOTAL NULLS PER SECOND (ALL LINES) = 12.30

PER LINE:

TO	UCC4	5.81	(883.21	BITS)	PER	SECOND
TO	UCC8	5.05	(768.24	BITS)	PER	SECOND
TO	UCC2	1.44	(218.89	BITS)	PER	SECOND

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14--

EXPERIMENT DURATION

FROM SEP 28, 1983 21:01:36.000 BBN-NMC TIME
 TO SEP 28, 1983 21:59:15.000 BBN-NMC TIME

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

34 CUM STAT'S (100% OF MAX.)
 TIME COVERED BY DATA = 3565.158 SECONDS

C30 IMP (EXA)

MESSAGE AND PACKET SIZE STATISTICS				LOG2 HISTOGRAM OF PACKET LENGTH			
HISTOGRAM OF MESSAGE LENGTH		HISTOGRAM OF MESSAGE LENGTH		LOG2 HISTOGRAM OF PACKET LENGTH		LOG2 HISTOGRAM OF PACKET LENGTH	
PACKETS	FROM HOSTS	INTO HOSTS	PACKETS	FROM HOSTS	INTO HOSTS	PACKETS	INTO HOSTS
1	20610	21920	16-BIT DATA	4	0	410	
2	189	1	WORDS				
3	46	2	0-1	12	1	30162	
4	0	17	2-3	29	0	527	
5	0	51	4-7	4945	4915	6616	
6	0	0	8-15	14849	15513	19636	
7	0	0	16-31	1287	1822	2568	
8	0	0	32-63				
TOTALS	20845	21991		21126	22251	59919	
MEAN/SEC (MSG)	5.85	6.17	(PKTS)	5.93	6.24	16.81	
MEAN BITS/SEC	2071.48	2236.90					
MEAN PKTS/MSG	1.01	1.01					
MEAN BITS/MSG	354.29	362.64					
MEAN BITS/PKT	349.58	358.41					

H2I: PKTS/SEC= 5.9 MSGS/SEC= 5.8
 I2H: PKTS/SEC= 6.2 MSGS/SEC= 6.2 PKTS & RFNMS = 12.1
 M2I: PKTS/SEC= 16.8
 I2M: PKTS/SEC= 16.8
 TSK: PKTS/SEC= 28.9

HOST MSG TOTALS	CSNET	BBN-N	DIV6-	FIBER
	-CIC	OC	TAC	-GW
TOTAL FROM	1732	2049	19	17045
CONTROL TO	1732	2049	19	17045

FAKE HOST MSG TOTALS	TTY	DEBUG	PC/TR	DS/ST
TOTAL FROM	0	0	0	0
CONTROL TO	0	0	0	0

CHANNEL ACTIVITY			
NEIGHBOR	PKTS OUT	BITS OUT	BITS/SEC
UCC4	19477	3.19E+06	895.93
UCC8	18576	3.60E+06	1010.25
UCC2	21866	3.79E+06	1063.04
TOTAL	59919	1.06E+07	2969.22
MEAN (DATA ONLY)	BITS/PKT OUT CHANNELS = 176.67		

# OF ROUND-TRIPS & MEAN RT TIME, TO FOLLOWING IMPS /SITE	#TRIPS, #MSEC/
CC3 1, 45 / UCC4 1214, 30 / UCC6	1079, 60
UCC7 5892, 51 / UCC8 7548, 32 / NCLB9	750, 78
MLB10 4124, 52 / UCC14 356. 11 /	

20964 ROUND-TRIPS TO ALL DESTINATIONS

TOTAL MEAN ROUND-TRIP DELAY = 44.17 MSEC.

TOTAL ROUTING UPDATES TRANSMITTED PER SECOND = 0.83

PER LINE:

TO UCC4	0.28	(49.80 BITS)	PER SECOND
TO UCC8	0.28	(49.80 BITS)	PER SECOND
TO UCC2	0.28	(49.80 BITS)	PER SECOND

AVERAGE NEIGHBORS IN ROUTING UPDATE = 2.72

TOTAL NULLS PER SECOND (ALL LINES) = 16.47

PER LINE:

TO UCC4	5.15	(783.20 BITS)	PER SECOND
TO UCC8	7.28	(1106.89 BITS)	PER SECOND
TO UCC2	4.03	(613.13 BITS)	PER SECOND

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

EXPERIMENT DURATION

FROM SEP 28, 1983 22:01:00.000 BBN-NMC TIME
 TO SEP 28, 1983 22:58:39.000 BBN-NMC TIME

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

34 CUM STAT'S (100% OF MAX.)
 TIME COVERED BY DATA = 3565.158 SECONDS

C30 IMP (EXA)

MESSAGE AND PACKET SIZE STATISTICS

HISTOGRAM OF MESSAGE LENGTH				LOG2 HISTOGRAM OF PACKET LENGTH			
PACKETS	FROM HOSTS	INTO HOSTS	16-BIT	HOSTS		CHAN	
			DATA	FROM	INTO	OUT	
1	17030	13712	WORDS				
2	816	5	0-1	10	0	599	
3	44	2	2-3	24	4	18363	
4	0	0	4-7	62	1	764	
5	0	2	8-15	4860	4808	6615	
6	0	0	16-31	11813	8323	14101	
7	0	1	32-63	2025	609	4401	
8	0	0					
TOTALS	17890	13722		18794	13745	44843	
MEAN/SEC (MSG)	5.02	3.85	(PKTS)	5.27	3.86	12.58	
MEAN BITS/SEC	1958.93	1263.23					
MEAN PKTS/MSG	1.05	1.00					
MEAN BITS/MSG	390.38	328.21					
MEAN BITS/PKT	371.60	327.66					

H2I: PKTS/SEC= 5.3 MSGS/SEC= 5.0
 I2H: PKTS/SEC= 3.9 MSGS/SEC= 3.8 PKTS & RFNMS = 8.9
 M2I: PKTS/SEC= 12.3
 I2M: PKTS/SEC= 12.6
 TSK: PKTS/SEC= 21.5

HOST MSG TOTALS	CSNET	BBN-N	DIV6-	FIBER
	-CIC	OC	TAC	-GW
TOTAL FROM	1260	305	20	16305
CONTROL TO	1260	305	20	16305

FAKE HOST MSG TOTALS	TTY	DEBUG	PC/TR	DS/ST
TOTAL FROM	0	0	0	0
CONTROL TO	0	0	0	0

CHANNEL ACTIVITY

NEIGHBOR	PKTS OUT	BITS OUT	BITS/SEC
UCC4	18516	5.07E+06	1421.24
UCC8	12023	2.47E+06	692.85
UCC2	14304	2.92E+06	819.01
TOTAL	44843	1.05E+07	2933.09
MEAN (DATA ONLY) BITS/PKT OUT CHANNELS =			233.19

# OF ROUND-TRIPS & MEAN RT TIME, TO FOLLOWING IMPS /SITE	#TRIPS, #MSEC/
CC3 2, 45 / UCC4 1491, 31 / UCC6	1098, 60
UCC7 5653, 57 / UCC8 3693, 31 / NCLB9	1653, 78
MLB10 4106, 55 / UCC14 305, 6 /	

18001 ROUND-TRIPS TO ALL DESTINATIONS

TOTAL MEAN ROUND-TRIP DELAY = 50.46 MSEC.

TOTAL ROUTING UPDATES TRANSMITTED PER SECOND = 0.85

PER LINE:

TO UCC4	0.28	(51.08 BITS)	PER SECOND
TO UCC8	0.28	(51.08 BITS)	PER SECOND
TO UCC2	0.28	(51.08 BITS)	PER SECOND

AVERAGE NEIGHBORS IN ROUTING UPDATE = 2.75

TOTAL NULLS PER SECOND (ALL LINES) = 12.02

PER LINE:

TO UCC4	4.48	(681.01 BITS)	PER SECOND
TO UCC8	3.79	(575.91 BITS)	PER SECOND
TO UCC2	3.75	(569.43 BITS)	PER SECOND

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

EXPERIMENT DURATION

FROM SEP 28, 1983 23:00:24.000 BBN-NMC TIME
 TO SEP 28, 1983 23:59:48.000 BBN-NMC TIME

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

35 CUM STAT'S (100% OF MAX.)
 TIME COVERED BY DATA = 3670.016 SECONDS

C30 IMP (EXA)

MESSAGE AND PACKET SIZE STATISTICS

HISTOGRAM OF MESSAGE LENGTH				LOG2 HISTOGRAM OF PACKET LENGTH				CHAN OUT
PACKETS	FROM HOSTS	INTO HOSTS		16-BIT DATA	HOSTS FROM	HOSTS INTO		
1	9919	8932		0-1	0	0	62	
2	14	1		2-3	1	1	11261	
3	1	4		4-7	1	0	146	
4	0	0		8-15	4009	4003	5652	
5	0	2		16-31	5378	4157	5809	
6	0	0		32-63	561	795	1119	
7	0	0						
8	0	0						
TOTALS	9934	8939			9950	8956	24049	
MEAN/SEC (MSG)	2.71	2.44	(PKTS)		2.71	2.44	6.55	
MEAN BITS/SEC	869.18	831.38						
MEAN PKTS/MSG	1.00	1.00						
MEAN BITS/MSG	321.11	341.33						
MEAN BITS/PKT	320.59	340.68						

H2I: PKTS/SEC= 2.7 MSGS/SEC= 2.7
 I2H: PKTS/SEC= 2.4 MSGS/SEC= 2.4 PKTS & RFNMS = 5.1
 M2I: PKTS/SEC= 6.6
 I2M: PKTS/SEC= 6.6
 TSK: PKTS/SEC= 11.7

HOST MSG TOTALS	CSNET	BBN-N	DTV6-	FIBER
	-CIC	OC	TAC	-GW
TOTAL FROM	1136	4131	20	4647
CONTROL TO	1136	4131	20	4647

FAKE HOST MSG TOTALS	TTY	DEBUG	PC/TR	DS/ST
TOTAL FROM	0	0	0	0
CONTROL TO	0	0	0	0

CHANNEL ACTIVITY

NEIGHBOR	PKTS OUT	BITS OUT	BITS/SEC
UCC4	12331	2.10E+06	573.05
UCC8	8888	1.77E+06	481.24
UCC2	2830	3.99E+05	108.71
TOTAL	24049	4.27E+06	1163.01
MEAN (DATA ONLY) BITS/PKT OUT CHANNELS =			177.48

# OF ROUND-TRIPS & MEAN RT TIME, TO FOLLOWING IMPS /SITE #TRIPS, #MSEC/									
UCC4	5585,	28 /	UCC6	1145,	58 /	UCC7	412,	47	
UCC8	2445,	29 /	NCLB9	1,	77 /	MLB10	162.	53	
UCC14	315,	6 /							

10065 ROUND-TRIPS TO ALL DESTINATIONS

TOTAL MEAN ROUND-TRIP DELAY = 32.30 MSEC.

TOTAL ROUTING UPDATES TRANSMITTED PER SECOND = 0.82

PER LINE:

TO UCC4	0.27	(49.14 BITS)	PER SECOND
TO UCC8	0.27	(49.14 BITS)	PER SECOND
TO UCC2	0.27	(49.14 BITS)	PER SECOND

AVERAGE NEIGHBORS IN ROUTING UPDATE = 2.69

TOTAL NULLS PER SECOND (ALL LINES) = 6.41

PER LINE:

TO UCC4	2.98	(452.35 BITS)	PER SECOND
TO UCC8	2.56	(388.94 BITS)	PER SECOND
TO UCC2	0.87	(132.37 BITS)	PER SECOND

--14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14-----14---UCC14---

1.26% [21250-21252] CRA
 .77% [21313-21317] SZE
 .10% [21325-21331] SPL
 .92% [21341-21345] SNZ
 .10% [21404-21411] ARR
 .25% [21442-21460] SHFLUP
 .07% [21461-21467] SHFLUP1
 .04% [21514-21515] SHFROT
 .02% [21516-21516] SHFRR
 .02% [21530-21530] SHFLR
 .58% [21531-21541] SHFLR1
 .08% [21575-21600] SHFINT
 .06% [21601-21603] SHFRET
 .03% [21632-21634] JFFO
 .03% [21635-21637] JFFO.NZ
 .01% [21640-21641] JFFO.FIRST8
 .02% [21666-21667] JFFO.SECOND8
 .01% [21670-21671] JFFO.THIRD4
 .02% [21702-21703] JFFO.FOURTH4
 .01% [21704-21707] JFFO.SEVENTH2
 .04% [21710-21713] JFFO.EIGHTH2
 .33% [21726-21765] Q.EMQ
 .08% [21766-21775] Q.DEQ
 .51% [21776-22026] Q.DEQ.RMQ
 .19% [22027-22052] Q.RMQ
 .09% [22073-22103] Q316.DEQ
 .51% [22275-22307] SOFT
 .12% [22310-22312] SOFT.INSTR
 .03% [22313-22315] SOFT.SCAN
 .15% [22325-22327] INT.INSTR
 .20% [22330-22333] FAST.LNSTR
 .14% [22334-22342] INT.SCAN
 .04% [22343-22344] EAO
 1.32% [22345-22347] EAOI
 .45% [22350-22350] MBR.MAR.LS
 .04% [22351-22352] EAOX
 .03% [22356-22356] MBR.X..LS
 .18% [22357-22361] EA1
 .04% [22362-22365] EA1I
 .25% [22366-22371] EA1X
 .12% [22372-22375] EA1IX
 2.94% [22376-22403] JMP1
 3.37% [22413-22416] STAO
 .56% [22417-22423] STA1
 .04% [23233-23234] DUMMY
 .12% [23241-23246] IO316.INH
 .39% [23247-23262] IO316.ENE
 .08% [23366-23375] IO316.SPK
 .13% [23376-23412] IO316.TDV
 .32% [23413-23432] IO316.RFI
 .01% [23433-23436] RFI.TO.READY
 .08% [23443-23450] RFI.TO.TIMING
 .04% [23451-23454] IO316.PCB
 .07% [23455-23463] IO.GOADSKIP
 .11% [23464-23502] IO.GOAD
 .33% [23610-23627] IO.EMQ.TIMING

.25% [23630-23635] TI.TOP
3.13% [23636-23650] TI.LOOP
.06% [23651-23652] TI.INT
.26% [23653-23703] TI.HERE
.45% [23704-23742] IO.RMQ.PENDING
.13% [24022-24027] IO.FIND.PHEDR
.22% [24030-24064] PM.SCAN
.02% [24074-24075] SCAN.FROM.PENDIN
.02% [24076-24077] SCAN.BOTTOM
.02% [24100-24101] SCAN.DUMMY
.06% [24102-24107] SCAN.SCAN
.02% [24110-24111] SCAN.ATTN1
.18% [24120-24131] SCAN.HAVE.PRIORI
.06% [24304-24306] SCAN.SAME
.06% [24311-24316] IO.CLOCK
.07% [24317-24331] CLOCK.AGAIN
.02% [24332-24333] CLOCK.EXIT
1.65% [24510-24512] IO.RET
3.24% [25476-25512] CM1I.INT
.03% [25513-25517] CM1I.GOING
.03% [25554-25556] CM1I.DATA
1.25% [25633-25642] CM1O.INT
2.14% [25643-25653] CM1O.IDLE
.03% [25670-25674] CM1O.DATA
.08% [25675-25704] CM1O.LOW
.02% [25705-25706] CM1O.SEND
.06% [25707-25714] CM1O.SEND1
.06% [25751-25753] CM1.CRC, CM1.CRC.PATC
.06% [25754-25756] CM1.CRC.PATB
.10% [25757-25763] CM1.CRC.PATA
.14% [25764-25772] CM1.CRC.PATD

.69% Overhead
4.00% General I/O
3.52% Console I/O
74.28% Instruction Emulation
2.74% Clock I/O
5.91% Process Management
8.87% ARPANET Trunk (MII) Driver