




BlackBerry 7100g Keypad Cover Replacement

Written By: Tristan French



INTRODUCTION

How to replace the BlackBerry 7100g keypad cover.

TOOLS:

- [Spudger \(1\)](#)
- [T6 Torx Screwdriver \(1\)](#)
- [iFixit Opening Tools \(1\)](#)

Step 1 — Battery




- Turn over your BlackBerry 7100g so that the back cover is facing up.
- Locate the battery cover release button near the bottom of the back panel.

Step 2




- Push down on the release button with one thumb.
- Slide the battery cover off with the other thumb.

Step 3



- Remove the battery from the battery housing by flipping up the top of the battery.

Step 4 — Housing



- Locate the silver strip near the top of your BlackBerry.
- Use a plastic opening tool to pry off the edge of the silver lining.
- Slide the tool along the length of the silver strip to completely remove it.

Step 5



(i) Do not lose the screws. They are quite small and can easily be misplaced.

- Locate and unscrew the four (4) screws using a T6 screwdriver.

Step 6



(i) The keypad cover may fall out of the housing when prying the housing apart.

- Tightly pinch the top of the front and back halves of the housing.
- Carefully pry the two halves of the housing apart.

Step 7



- You can now easily remove the "guts" of the phone from the housing.

Step 8 — Keypad Cover



- Remove the keypad cover.
- Insert the new keypad cover.
- You are done replacing your keypad cover.

To reassemble your device, follow these instructions in reverse order.