



Blackberry Bold 9900 Power/Volume Button Replacement

This guide will show you how to replace the power/volume button on the Blackberry Bold 9900.

Written By: Sarah Westberg



This document was generated on 2020-01-23 12:11:50 AM (MST).

INTRODUCTION

This replacement guide will show you how to replace your Blackberry Bold 9900 power/volume button which is attached to the midframe. You will need to follow several prerequisite guides in order to get to this point but it will help you increase the length of Blackberry's life and function.

TOOLS:

- [Spudger](#) (1)
- [T5 Torx Screwdriver](#) (1)

Step 1 — Battery




- Place phone screen down.
- Use your finger to lift upward on the battery case.
- Pull the cover away from the battery.

Step 2




- Lift the edge of battery with the green stripe upward to remove battery.

Step 3 — Memory Card




- The Memory Card is located inside the red rectangle.
- To remove the Memory Card, push and slide the card inward towards the top of the phone. It will be ejected.

Step 4 — SIM Card




- The SIM Card is located where the red rectangle is shown.
- To remove SIM Card, push the card inward towards the top of the phone then release. The SIM card will be ejected.

Step 5 — Keyboard



- Lift the bezel at the bottom of the phone up and peel it away from the phone.

Step 6




- Remove the two exposed screws using the T5 Torx screwdriver.

Step 7




- Now lever the keyboard up using the screwdriver in the indicated hole.

Step 8



- The keyboard is attached via a ribbon cable. Pull the cable up to remove the keyboard.

Step 9 — Back Case



- Using the T5 Torx Screwdriver, remove the four torx screws that are located on the bottom half of the device

Step 10



- Now, carefully and gently using your fingers, lift and remove the assembly from the back case.

Step 11 — Power/Volume Button



- Use the black nylon spudger to pop the press fit connector up from the lower left corner of the motherboard.

Step 12



- Lift the midframe, which contains the power/volume buttons, off of the motherboard and screen.

To reassemble your device, follow these instructions in reverse order.