



# Blackberry Curve 8330 Keyboard Replacement

Replace a damaged or non-functional QWERTY keyboard.

Written By: Nolan Reker



 **TOOLS:**

- [iFixit Opening Tools \(1\)](#)
- [T5 Torx Screwdriver \(1\)](#)
- [T6 Torx Screwdriver \(1\)](#)

## Step 1 — Remove Back Cover



*(i)* We did not have an actual back cover or battery for the phone we were given. Therefore, the first couple of steps will be without pictures.

- Hold the phone with the back side facing you.
- Press down on the silver tab towards the bottom end of the phone.
- Carefully lift up the back casing to reveal the battery.

## Step 2 — Remove Battery



- Put your finger on the top left corner of the battery and lift the battery up and out of its housing.
- The phone should now look like this.

## Step 3 — Keyboard



- Remove the two top screws using a T5 Torx screwdriver.

## Step 4



- Use a plastic opening tool to pry the edges of the bottom cover until it snaps loose.
- The cover will now pull off easily.

## Step 5



- Use a plastic opening tool to pry between the front and back cover.
- Start prying from wherever it is easiest to separate the silver and black plastic of the covers.

***i*** There are 5 securing clips on the front panel to disconnect.

**⚠** Pry gently to prevent breaking the plastic clips when removing the front panel.

- Once all the clips have been freed, the front cover will lift away from the phone.

## Step 6



- Lift the flexible keypad away from the device. It should come off easily.

## Step 7



- Use a T6 Torx Screwdriver to remove the four corner screws on the keyboard's housing.
- Lift the keyboard frame away from the device.

**(i)** There may be a small amount of adhesive at the bottom of the frame that needs to be pulled away.

To reassemble your device, follow these instructions in reverse order.