



Dell Chromebook 11-3120 Battery Replacement

Replace the battery of a Dell Chromebook 11-3120.

Written By: Dalton D



INTRODUCTION

This guide will help you replace the battery of a Dell Chromebook 11-3120. Please have a safe, static-free place where you can place the battery after it has been removed from the device.

TOOLS:

- [Phillips #0 Screwdriver](#) (1)
 - [Spudger](#) (1)
-

Step 1 — Remove screws



- Flip the device over so the bottom is facing up
- Remove the 7 visible Philips screws from the device's bottom cover

Step 2



- Insert a thin prying tool into the front (facing the user) corner between the rubber bumper and the plastic case to pop several latches.
- Starting from the partially-opened corner, pull the case away from the device in a hinging motion. I rotated the computer so that the opened corner faced me in the image.

-
- The image shows the internal components of a Dell Latitude E6410 laptop. The motherboard is visible with various components like the CPU, RAM, and connectors. The battery is a large, black, rectangular unit with a label that includes safety warnings and technical specifications. A hand is using a screwdriver to remove a screw from the bottom cover. The bottom cover has two screws highlighted with red circles. The battery label includes the following text:
- DELL**
Battery Question?
Go to www.dell.com
- Cells made in Korea
Assembled in China
- CAUTION** Do not expose the battery to temperatures above 65°C (149°F).
See the manual for safety instructions.
PRÉCAUTION Ne pas soumettre la batterie à des températures supérieures à 65°C (149°F). Voir le manuel pour des instructions de sécurité.
VORSICHT! Der Akku darf niemals Temperaturen über 65°C ausgesetzt werden. Siehe Bedienungsanleitung für die Instruktionen de Sicherheit.
- 注意：避免将电池暴露于高温环境。
请参见用户手册，以获取有关安全操作的说明。
警告：请勿将电池暴露于高温环境。
请参见用户手册，以获取有关安全操作的说明。
- Li-ion
11.1V
4400mAh
3.70Ah
- 安全警告
请勿将电池暴露于高温环境。
请参见用户手册，以获取有关安全操作的说明。
- RECYCLED
Li-ion
Recycle Only
- DECLARATION - Conforming to IS 16046 : 2012, R-41016462

- Page 4 of 5

Step 5



- Lift the battery straight out of the case and place it in a safe, static-free place

To reassemble your device, follow these instructions in reverse order.