




# Dell Inspiron 1428 Hard Drive Replacement

Written By: Terrence15




## INTRODUCTION

In this guide, we will show you how to remove and replace the Hard Drive.

### TOOLS:

- Essential Electronics Toolkit (1)

## Step 1 — Remove the Screws




**⚠** **WARNING:** Before working inside your computer, read the safety information that shipped with your computer. Follow the procedures in ["Before You Begin"](#).

**⚠** **CAUTION:** To avoid electrostatic discharge, ground yourself by using a wrist grounding strap or by periodically touching an unpainted metal surface (such as a connector on your computer).

**⚠** **CAUTION:** Hard drives are extremely fragile. Exercise care when handling the hard drive.


- Remove the two screws that secure the hard-drive cover to the computer base.

## Step 2 — Pry out the Hard-Drive Cover




- Pry out the hard-drive cover using your finger.

## Step 3 — Remove the Screws




- Remove the two screws that secure the hard-drive assembly to the computer base.

## Step 4 — Disconnecting the Hard Drive Assembly




- Pull the pull-tab on the hard-drive assembly towards the right to disconnect the hard-drive assembly from the system board connector.

## Step 5 — Lifting the Hard-Drive Assembly




- Lift the hard-drive assembly out of the computer base.

## Step 6 — Remove the Screws




- Remove the four screws that secure the hard drive to the hard-drive cage.

## Step 7 — Placing the Hard Drive




- Place the **NEW** hard drive in the hard-drive cage.

## Step 8 — Replace the Screws




- Replace the four screws that secure the hard drive to the hard-drive cage.

## Step 9 — Placing the Hard-Drive Assembly




- Place the **NEW** hard-drive assembly in the computer base.

## Step 10 — Connecting the Hard-Drive Assembly




- Slide and connect the hard-drive assembly to the system board connector.

## Step 11 — Replace the Screws




- Replace the two screws that secure the hard-drive assembly to the computer base.

## Step 12 — Align the Tabs



- Align the tabs on the hard-drive cover with the slots on the computer base and snap the hard-drive cover into place.

## Step 13 — Replace the Screws



- Replace the two screws that secure the hard-drive cover to the computer base.