



Dell XPS 13 Solid State Drive (SSD) Replacement

This guide will explain how to replace the solid state drive (SSD) in the Dell XPS 13 9350.

Written By: Jay



This document was generated on 2019-10-12 12:42:17 PM (MST).

INTRODUCTION

[**Click here**](#) for the updated version of this guide. The guide you are currently viewing is archived here for historical purposes only.

TOOLS:

- [T5 Torx Screwdriver](#) (1)
- [iFixit Opening Picks set of 6](#) (1)
- [Spudger](#) (1)
- [Phillips #00 Screwdriver](#) (1)

Step 1 — Back Cover



- Remove the eight 4 mm T5 Torx screws from the bottom cover.

Step 2



- Use a plastic opening tool to pry open the 'XPS' flap in the middle.

Step 3



- Remove the single Phillips screw hidden beneath the flap.

Step 4



- Use opening picks or a plastic pry tool to pry open the case clips, beginning from the back edge.

Step 5



- Remove the bottom cover.

Step 6 — Solid State Drive (SSD)



- Remove the black, 4 mm Phillips #000 screw on the right of the SSD.

(i) The SSD card will pop up at a 45-degree angle after the screw is removed.

Step 7



- Gently lift the SSD card with your hand to pull it up and to the right.

To reassemble your device, follow these instructions in reverse order.