



Disassembling 2010-2014 Ford Mustang Center Console

This guide will explain how to disassemble the center console of your 2010-2014 Ford Mustang containing the stereo and climate controls.

Written By: Christopher Pell



This document was generated on 2020-04-16 03:09:58 PM (MST).

INTRODUCTION

Whether for installing a new stereo system, or just for checking for disconnected wires, the center console of a car often needs to be removed. This guide will show you how to remove the center console of your 2010-2014 Ford Mustang.

TOOLS:

- [7mm socket wrench \(1\)](#)
- [iFixit Opening Tools \(1\)](#)
- [Socket Set \(1\)](#)

Step 1 — Disassembling 2010-2014 Ford Mustang Center Console



- Open the rear part of the middle console.

Step 2



- Grip the right side of the console and pull up towards the passenger seat to remove it.

Step 3



- Locate the two bolts under the air conditioning controls at the bottom of the face plate.
- Loosen these two bolts with a basic socket wrench suited for 7mm bolts.

Step 4



- Wedge a spudger or plastic opening tool (in place of the screwdriver shown) under the top of the face plate.
- Apply pressure until the corners "pop" out of place.

Step 5



- Inspect the interior of the center console for damaged wires or other faulty components.

To reassemble your device, follow these instructions in reverse order.