




Dissasembling Nokia 8290 Charging Port

Use this guide to replace your Nokia 8290's charging port.

Written By: Parker Niebauer



INTRODUCTION

Installing a new charging port may be necessary if you are having trouble charging your battery. Installation should only be done as a last resort, after trying other possible solutions as listed in the [Nokia 8290 Troubleshooting Guide](#). Installation requires no prior knowledge of mobile phone charging ports.

TOOLS:


- [64 Bit Driver Kit](#) (1)
- [Tweezers](#) (1)

Step 1 — Front Cover



- Locate the small button on the top of the phone.
- Depress the button.
- With your other hand, pull the front cover away from the phone.

Step 2 — Installing Nokia 8290 Charging Port



- Remove all six 5.3 mm long T6 screws.
- Remove the circuit board/faceplate sub-assembly from the back of the phone.

 Take care to place screws in a safe location.


Step 3



- Use tweezers to remove the indicated part.

(i) The part is black with six metal connectors. Its approximate dimensions are 12.3 mm x 8.4 mm x 8.2 mm.


Step 4



- There is another part located directly underneath the part removed in the previous step. Use tweezers to remove this part as well.

(i) The part is black with four rectangular spaces in the bottom. Its approximate dimensions are 10.4 mm x 6.6 mm x 4.5 mm.

Step 5



- After removing the two parts, locate the charging port.
- Use tweezers to remove the charging port.

To reassemble your device, follow these instructions in reverse order.