



Fairphone 1 Midframe Replacement

Replace the Midframe in your Fairphone.

Written By: Sam Goldheart



INTRODUCTION

Use this guide to remove the plastic midframe from your Fairphone to access internal components.

TOOLS:

- [iFixit Opening Picks set of 6](#) (1)
 - [Phillips #000 Screwdriver](#) (1)
-

Step 1 — Back Cover



-  There is a small indentation in the side of the phone near the bottom of the back cover.
- With the indentation as leverage, use your fingernail to pry the bottom portion of the back cover from the phone.

Step 2



- Slide the back cover down and remove it from the phone.

Step 3 — Battery



- i** There is a small indentation in the back of the phone just below the battery.
- Use a fingernail in this indentation to push the battery toward the top of the phone
 - Pull the battery out away from the phone.

Step 4



- Remove the battery from your Fairphone.

Step 5 — SIM and MicroSD Card



- Use your finger to slide the SIM card straight down out of its tray.
- Remove the SIM card from your Fairphone.
- ⓘ Repeat this procedure if you have a second SIM card.
- ⚠ Be sure to remove all SIM cards before servicing your phone.

Step 6



- If you have a microSD card, use your finger to slide it straight out of its slot.
- Remove the microSD card from your phone.

Step 7 — Midframe Assembly



- Remove the five 3.9 mm Phillips #000 screws securing the midframe to the display assembly.

Step 8



- i** The midframe is secured to the display assembly by several small plastic clips.
- Use an opening pick to carefully pry the midframe away from the display assembly.
 - Start just below the volume rocker and work your way down toward the bottom of the phone, freeing the plastic clips along the side.

Step 9



- Carefully round the corner, separating the midframe from the display assembly.

Step 10



- ⓘ After rounding the next corner, the midframe should be free along the bottom and the sides.

Step 11



- Run the opening pick and pry along the top seam.

 To avoid bending or damaging the opening picks, do not pry near to the power switch, USB port, or headphone jack.

Step 12



- Separate any remaining clips and remove the midframe from the phone.

Step 13 — Midframe



- ❗ The speakerphone speaker is held to the midframe with some mild adhesive.
 - Use the tip of a spudger to pry the speaker off of the midframe.

Step 14



- Remove the speaker from the midframe.

To reassemble your device, follow these instructions in reverse order.