




# Fairphone 2 Microphone Module Replacement

This guide will show you how to replace the microphone module of the Fairphone 2.

Written By: Tobias Isakeit



## INTRODUCTION

This guide will show you how to replace the microphone module of the Fairphone 2.

### TOOLS:

- Phillips #0 Screwdriver (1)

### PARTS:

- Fairphone 2 Microphone Module (1)

## Step 1 — Slim Case




- Pick a corner of your slim case and get between the two parts with your thumb's fingernails.
- Pull up the back part of the slim case to separate the small snap fit connections.
- Remove the back part of the slim case.

## Step 2




- Get in between the front part of the slim case and the phone's body with your thumb nail.
- Separate the snap fit connectors on the front part by pulling it to the side and pushing against the display.

## Step 3



- Remove the front part of the slim case.

## Step 4 — Battery



- Push the battery toward the top of the phone.
- Pull the battery out away from the phone.

## Step 5 — Display Assembly



- After taking out the battery you can unlock the display assembly.
- Flip the two blue switches to the inner position.
- Slide the display assembly towards the bottom of the phone.

## Step 6



*(i)* Another possible way of sliding the display assembly open.

## Step 7




- Take off the display assembly.

## Step 8 — Microphone Module



- Remove the four Phillips #0 screws that are factory-marked with blue circles.

## Step 9



- Take out the whole microphone module.

To reassemble your device, follow these instructions in reverse order.

Information on what to do with the old module can be found on the [FairPhone support page](#) and in the [FairPhone forum](#).