



# Galaxy J3 Prime LCD Screen Replacement

How to take a Galaxy J3 Prime apart.

Written By: Brian Brown

## INTRODUCTION

In this guide, you will learn how to completely take apart a Galaxy J3 Prime and put it back together again.

A video is also available for additional help.

## TOOLS:

- [Spudger](#) (1)
- [Small phillips head screw driver](#) (1)
- [Tweezers](#) (1)
- [iOpener](#) (1)
- [Hair Dryer or Heat Gun](#) (1)

*Optional if you aren't using a iOpener.*

## Step 1 — Back Cover and Battery



- Remove the back cover and battery.

## Step 2 — Loosen Adhesive



- Heat up the screen to loosen the adhesive.
- You can use a iOpener or a hair drier, but make sure you don't get the phone too hot.

## Step 3



- Put a spudger between the phone frame and the front display.

## Step 4 — Remove Plastic Bracket



- Remove the plastic bracket that will be visible when you pry up the screen.

## Step 5 — Remove Screen



- Gently pull up on the LCD screen adhesive to remove the screen.

## Step 6 — Remove Housing Screws



- Remove the screws on the back of the phone frame that are holding the housing of the phone together.

## Step 7 — Pull Up Screen



- Now that all of the screws have been removed, pull up the frame with a screwdriver or spudger.
- Be gentle so you don't break anything.

## Step 8 — Removing the Motherboard



- Disconnect the metal flex cable from the charging port.
- Remove the Motherboard from the housing.

To reassemble your device, follow these instructions in reverse order.