




Garmin Fenix 2 Motherboard Replacement

How to replace the motherboard in the Garmin Fenix 2

Written By: Brandon Barger



INTRODUCTION

We are going to remove the motherboard out of the Garmin Fenix 2 watch. You will need a Torx T9 screwdriver along with a nylon spudger for this fix.

TOOLS:


- [Spudger \(1\)](#)
- [T9 Torx Screwdriver \(1\)](#)

Step 1 — Battery



- Use a Torx T9 screwdriver to remove these four .8mm screws and separate the housing.

Step 2




- Use a spudger tool to disengage the power ribbon from the main board. Once the ribbon is disconnected you can separate the bottom piece of the housing that holds the battery.

Step 3




- Use the spudger tool again and wedge it in between the battery and the housing, pry until the battery starts to separate from the adhesive holding it in place. Once you have the battery disconnected you are ready to replace it.
- ⚠** Despite the fact that the metal spudger is shown being used in this step, make sure to use a plastic opening tool or nylon spudger to pry up the battery. The metal spudger has a much larger chance of puncturing the battery, and thus should not be used.

Step 4 — Motherboard



- Use a spudger to pry open the power ribbon from the main board.

Step 5




- Use your Torx T9 screwdriver to remove the one .8mm screw that holds the main board to the watch housing.

Step 6




- Use the spudger to pry the motherboard out of the housing.

Step 7



- Once removed simply separate the digitizer from the main board.

Step 8



- Lastly use your spudger tool to pry the data ribbon open from the motherboard. Once the ribbon is removed the board will be free and you can replace the board.

To reassemble your device, follow these instructions in reverse order.