



# HP Pavilion x360 m3-u103dx HP Pavilion x360 m3-u103dx Keyboard Replacement

How to replace the keyboard for the HP Pavilion x360 m3-u103dx.

Written By: Teresita Aragon



## INTRODUCTION

In this guide you will be required to remove the keyboard and disconnect three wires from the device in order to replace the keyboard. You will need to use a iFixit Pro Tech Toolkit.

This task requires patience and attention to detail.

## TOOLS:

- [Metal Spudger \(1\)](#)
- [Phillips #00 Screwdriver \(1\)](#)
- [Heavy-Duty Spudger \(1\)](#)


## Step 1 — Keyboard



- Power off Device.

 Working device while it is powered on may cause damage to laptop or electric shock.

## Step 2



- Flip over laptop
- Remove the rubber foot with a Metal Spudger

## Step 3



- Remove the screws from the bottom of the laptop using a Phillips 00 Screwdriver.
  - 5 Phillips 2.4 x 5.7 mm screws.
  - 5 Phillips 2.0 x 5.0 mm screws.
- *(i)* Make sure to keep different screw types separated.


## Step 4



- Flip the laptop over to screen and keyboard side.
- Using a Metal Spudger pop open keyboard from base of laptop.

**⚠** Be cautious of three wires on the inside of the keyboard connecting it to the motherboard.

## Step 5



- Disconnect the three connected cable ribbons connected to the motherboard by gently pulling them out of their connectors.

## Step 6



- After ribbon cables have been disconnected, carefully lift up keyboard to disconnect from base of laptop.

To reassemble your device, follow these instructions in reverse order.