



Huawei P9 Lite Battery Replacement

Replace the battery in your Huawei P9 Lite.

Written By: Tobias Isakeit



INTRODUCTION

Use this guide to replace the old battery in your Huawei P9 Lite.

TOOLS:

- iFixit Opening Picks set of 6 (1)
- Phillips #00 Screwdriver (1)
- Tweezers (1)
- iOpener (1)

PARTS:

- [Huawei P10 Lite, P9, P9 Lite, and Honor 8 Replacement Battery \(1\)](#)

Step 1 — Back Cover




- Use an opening pick to unclip the rear cover, starting from the bottom corner.
- Work your way around counterclockwise and carefully pry the plastic tabs open one by one.

Step 2



- There is adhesive underneath the back cover that holds it to the battery and the metal plate at the top.
 - ⚠ Be careful with the flex cable at the right hand side.
- Twist the opening pick to lever the back cover away and loosen it from the adhesive.

Step 3




- When the back cover is freed from the adhesive you can pop it off by hand completely.

Step 4 — Loudspeaker




- On the bottom of the phone remove the following screws:
 - Three 2.9 mm Phillips #00 screws
 - Four 3.8 mm Phillips #00 screws
- Now you can grab the loudspeaker unit and take it out.

Step 5 — Motherboard Shield



- Remove the nine Phillips #00 screws that secure the metal shield plate.
 - *(i)* Some screws may be covered with tamper proof stickers. Remove them to ensure a proper seating for your driver.

Step 6



! Do not remove the shield plate yet, it is attached by a connector and an adhered cable.


- Use a spudger to disconnect the fingerprint sensor from the motherboard.
- Peel the NFC antenna cable off of the metal plate.

Step 7 — Battery



- Disconnect the motherboard flex cable on both ends and take it away.

Step 8



- Peel off the NFC antenna from the battery.
 - ⚠ Be careful not to rip or crease the antenna.
 - ⓘ If you are just removing the battery to get to the display, you can leave the NFC on the battery.
- Unplug the battery connector.

Step 9



- Slide the spudger under the battery at the place shown in the picture and pry it loose slowly.
⚠ Avoid bending the battery and reheat if necessary.
- ⚠ Be careful not to damage the display flex cable that runs underneath the battery in the center.
- When reassembling your phone replace old adhesive with [double-sided tape](#) or [pre-cut adhesive strips](#).

To reassemble your device, follow these instructions in reverse order.