




# KitchenAid KSB5CR Fan Replacement

This guide will demonstrate how to remove the KitchenAid KSB5CR's fan.

Written By: Cameron Geehr



## INTRODUCTION

The fan cools down the motor and circuit board when the blender is operating.

### TOOLS:


- Phillips #2 Screwdriver (1)
- 8" Needle Nose Plier (1)

## Step 1 — Removing the Back Panel Part 1



- Remove the glass container and place the blender upside down on a solid surface.
- Remove the four rubber feet using the needle nose pliers.
- Remove the four #7.5 Phillips 25mm screws that were located underneath the rubber feet using the Phillips #2 screwdriver.

## Step 2 — Removing the Back Panel Part 2



- Lift the back panel up, sliding it along the power cord.

## Step 3 — Removing the Fan Chassis Part 1




- Remove the two #5 Phillips 95 mm machine screws using the Phillips #2 screwdriver.
- Remove the rubber O-ring by lifting it up.
- Remove the ribbon cable from the chassis by lifting it up.

## Step 4 — Removing the Fan Chassis Part 2



- Unhook the white wire that is looped around the peg by pulling it out of the clip.
- Repeat this process with the red wire on the other side of the chassis.
- Remove the end cap using the 8" needle nose pliers.
- Pull up the fan chassis.

## Step 5 — Removing the Fan



- Remove the fan by lifting it upwards.

***i*** This step is difficult and requires force. Use of both hands is recommended.

To reassemble your device, follow these instructions in reverse order.