



LG G3 Vigor Motherboard Replacement

This guide will go over the steps to removing and replacing your devices motherboard.

Written By: Jared Stickl




INTRODUCTION

Having technical issues with your LG G3 Vigor that are linked to your devices motherboard? You are in luck, this is the LG G3 Vigor motherboard replacement guide.

TOOLS:

- [Phillips #00 Screwdriver](#) (1)
- [iFixit Opening Tools](#) (1)
- [Spudger](#) (1)

Step 1 — Rear Case



- Locate the notch on the bottom right of the phone.

Step 2



- Gently pull the cover on the back of the phone off to locate the battery.

Step 3 — Battery




- Remove the battery by lifting from the slot at the bottom of the battery.

Step 4 — Midframe




- Remove the twelve Phillips #00 screws securing the midframe to the rest of the phone.

Step 5





- Work a plastic opening tool around the perimeter of the phone to separate the midframe from the rest of the phone.

Step 6 — Rear Facing Camera




- Use the spudger to gently unplug the ribbon cable connected to the motherboard. Then remove the rear facing camera.

Step 7 — Front Facing Camera




- Use the spudger to gently unplug the ribbon cable connected to the motherboard.
- Remove the front camera.

Step 8 — Motherboard



- Use the flat edge of a spudger to disconnect the motherboard ribbon connector.

Step 9



- Use the pointed end of a spudger to push back the two motherboard retaining flaps.
- The motherboard should now be able to be lifted out of the device.

To reassemble your device, follow these instructions in reverse order.