




LG V20 Volume Button Replacement

This guide explains the steps required to remove the volume button from the LG V20.

Written By: Garrett Janney



INTRODUCTION

Exposure to dirt or the shock of dropping a phone can damage volume buttons and cause them to become unresponsive. This guide will lead you through all the steps required to get your LG V20's volume button out of the phone and ready for replacement.

TOOLS:

- [Phillips #00 Screwdriver](#) (1)
- [iFixit Opening Tools](#) (1)

Step 1 — Battery



⚠ Before disassembling your phone, discharge the battery below 25%. A charged lithium-ion battery can catch fire and/or explode if accidentally punctured.


- Use the flat end of a spudger and insert it in the small recess at the lower end of the battery.
- Use the spudger to lever out the battery and remove it.
- **(i)** You can do this with your fingers but take care not to puncture the battery with your fingernails.

Step 2 — Midframe Assembly



- Remove the sixteen 4mm Phillips #00 screws attaching the back cover to the motherboard.

Step 3



(i) The top and bottom frame section hold very tight to the mid frame. It is possible to pull them off with your hands. If you're not able to do so, use the following removal procedure:

- Use the flat end of a spudger and apply pressure to one of the corners of the frame section until you create a small gap.

Step 4




- Flip the phone and insert an opening pick in the gap you created.
- Slide the opening pick along the gap until the frame section pops out of its plastic clamps.

Step 5




- Remove the frame section.
- Repeat this procedure with the frame section on the other end of the phone.

Step 6



- The loudspeaker is attached to the cover of the motherboard. Use an opening pick to pry it up.


Step 7



(i) The cover of the motherboard is held in its place by several plastic clamps.

- Use an opening pick to pry up the motherboard cover at the right corner at the bottom of your phone until it pops out of the plastic clamp.

Step 8




- Slide the opening pick along the mid frame and flip it sideways to open the plastic clamps holding the motherboard cover in its place.

Step 9



- Remove the motherboard cover.

Step 10 — Volume Button



- Use the flat end of a spudger to slide the volume button out of its bracket and remove it.

To reassemble your device, follow these instructions in reverse order.