



MacBook Pro 13" Retina Display Early 2013 Battery Contact Board Replacement

Replace the Battery Contact Board in your MacBook Pro 13" Retina Display Early 2013.

Written By: Sam Goldheart



INTRODUCTION

Use this guide to replace the battery contact board.

TOOLS:

- MacBook Pro and Air 5-Point Pentalobe Screwdriver (1)
- iFixit Opening Tools (1)
- T6 Torx Screwdriver (1)
- Tweezers (1)

PARTS:

- MacBook Pro 13" Retina Battery Contact Board (1)

Step 1 — Lower Case



- Remove the following ten screws securing the lower case to the upper case:
 - Two 2.3 mm P5 Pentalobe screws
 - Eight 3.0 mm P5 Pentalobe screws

 Throughout this repair, [keep track of each screw](#) and make sure it goes back exactly where it came from to avoid damaging your device.

Step 2




- Wedge your fingers between the upper case and the lower case.
- Gently pull the lower case away from the upper case.
- Remove the lower case and set it aside.

Step 3




- ⓘ The lower case is connected to the upper case at the center, with two plastic clips.
- ⚡ During reassembly, gently push down the center of the lower case to reattach the two plastic clips.

Step 4 — Battery Connector





- Remove the plastic cover adhered to the battery contact board.

Step 5




- Remove the following screws securing the battery connector board to the logic board:
 - Two 2.8 mm T6 Torx screws
 - One 7.0 mm T6 Torx shouldered screw

Step 6



- Use tweezers to remove the small plastic cover located near the bottom right of the battery connector board.

Step 7



- Remove the wide head 6.4 mm T6 Torx screw securing the battery connector to the logic board assembly.

Step 8




- Carefully lift the battery connector board up off the logic board.
- It is recommended to bend the battery cables just slightly, to keep the board suspended up above the logic board and out of the way.

⚠ Do not fold the board completely over, or crease the cables, as this may damage the battery.

This document was generated on 2019-09-21 09:23:13 PM (MST).

Step 9 — Battery Contact Board



- Grasp the Interposer with tweezers.

(i) An interposer is the name for an interface that links one electrical connection to another. In this repair, it is the board connecting the battery to logic board.

- Lift the Interposer off the logic board and remove it.

⚠ Removing this board will ensure that the battery remains disconnected throughout your repair, preventing your computer from accidentally powering on. It's also a good idea to take it out so it doesn't fall out unexpectedly.

To reassemble your device, follow these instructions in reverse order.