




MacBook Pro 17" Unibody Hard Drive Bracket Replacement

Replace the large hard drive bracket in a MacBook Pro 17" Unibody.

Written By: Sam Goldheart



INTRODUCTION

Use this guide to replace the hard drive bracket nearest the front edge of the MacBook Pro 17" Unibody.


TOOLS:

- [Phillips #00 Screwdriver \(1\)](#)

PARTS:


- [MacBook Pro 17" Unibody Front Hard Drive Bracket \(1\)](#)

Step 1 — Lower Case



- Remove the following ten screws securing the lower case to the upper case:
 - Three 13.5 mm Phillips screws.
 - Seven 3 mm Phillips screws.

Step 2



- Wedge your fingers between the lower case and the vent, and lift upward to release the two clips holding the lower case to the upper case.
- ➡ During reassembly, carefully align the lower case and then press it firmly until both clips engage.
- Remove the lower case.


Step 3 — Battery



⚠ Whenever working near the logic board, it is always wise to first disconnect the battery to avoid short circuits.


- If present, grab the plastic tab attached to the battery connector and pull it toward the front edge of the device. For Late-2011 models the battery connector will not have a tab and is simply a plug that inserts straight down into the motherboard--to remove pry the plug straight up.
- **i** If the plastic tab is missing, use a spudger to pry the connector up from its socket.
- **↗** Pull the tab parallel to the face of the logic board.

Step 4 — Hard Drive



- Remove the two Phillips screws securing the hard drive bracket to the upper case.
- **i** These screws are captive to the hard drive bracket.

Step 5



- Remove the hard drive bracket from the upper case.

Step 6



- Use the hard drive's pull tab to lift it out of the upper case.

⚠ Don't try to completely remove the hard drive just yet! Its cable is still connected.

Step 7




- Pull the hard drive connector away from the body of the hard drive.
- Remove the hard drive from your MacBook Pro.

Step 8 — Hard Drive Bracket



- Remove the two 5 mm Phillips #00 screws securing the hard drive bracket to the upper case.

Step 9



- Tilt the outer hard drive bracket up toward the logic board and remove it from the rear case.

To reassemble your device, follow these instructions in reverse order.