



Motorola Moto G 1st Generation Midframe Replacement

This guide will show you how to open your Moto G to get to many of the parts you will be replacing.

Written By: Rebecca Montgomery



This document was generated on 2019-09-18 07:36:34 AM (MST).

INTRODUCTION

With a few simple steps, this guide shows you how to open your Moto G to get to the innards of your phone.

TOOLS:

- [iFixit Opening Tools](#) (1)
- [T5 Torx Screwdriver](#) (1)

Step 1 — Removing the Cover



- You can remove the outer cover on the back of the phone by using a plastic opening tool. After removal the inner back cover will be exposed as shown.
- This part is moderately difficult, especially if you've never taken the outer back cover off before this point.
- It may take you several tries, but please be patient. The cover is surprisingly flexible, but not enough to withstand a lot of pressure.

Step 2



- Shut down the phone.
- Push SIM card until it pops out.
- Remove SIM card.

Step 3 — Removing the Back Plate



- Using a T5 Torx screwdriver head, take out the 14 screws (3.5 mm diameter and 5 mm long) that hold the back plate in place.
- Make sure to keep all of the screws together, as they are very easily lost.
- The magnetic project mat or a container is a great way to keep all the little metal screws as well as other small metal pieces from being lost.

Step 4 — The Inside of your Phone



- Use the plastic opening tool to take out the inner back cover after all the screws have been removed.
- This will expose the motherboard and the attached battery.
- Take note that once the inner back cover is removed the volume and power buttons on the side can easily fall out or be removed.

To reassemble your device, follow these instructions in reverse order.