



Motorola Moto G3 Battery Replacement

When the battery is not working properly or as the battery life drains too easily, this guide will show how to replace the battery altogether.

Written By: Irkan Notta



INTRODUCTION

[Click here for an updated version of this guide.](#) The version you are viewing is retained for historical purposes.

If your battery is swollen, [take appropriate precautions](#).

TOOLS:

- iFixit Opening Tools (3)
- iFixit iOpener (1)
- Precision Tweezers Set (1)

Step 1 — Prerequisite Guide



- Use the plastic opening tool to open the back cover as shown in the photo.

Step 2




- Heat an iOpener in the microwave for 30 seconds.
- Place the heated iOpener on all four edges of the screen for approximately 2 minutes.

Step 3




- Apply the plastic opening tool on the edge of the screen near the front camera.
- After creating enough space, allow the opening tool to be inserted on the side of the phone.
- Create another space on the other side of the screen.
- Leave the opening tool inserted.
- Carefully apply the larger plastic opening tool by sliding it through the longer edge of the screen.

Step 4




- A strip will be attached to the motherboard as shown.
- Using tweezers, carefully detach the strip from the motherboard.

Step 5 — Battery



- With a T4 screwdriver, remove the 10 "yellow" 2mm screws and 4 "black" 2mm screws.

Step 6





- Use the metal spudger and lift the back cover on the bottom side of the phone (this is attached to the motherboard).

Step 7



- Remove the red and black battery cable from its port using tweezers.

Step 8



- Use the same tweezers to remove the red battery from where it is placed.

To reassemble your device, follow these instructions in reverse order.