




Motorola Moto G4 Plus Motherboard Replacement

Remove and replace your motherboard as a prerequisite to other guides.

Written By: Andre Rives




INTRODUCTION

This guide will walk you through the process of replacing the motherboard in a Motorola Moto G4 Plus phone.

TOOLS:

- [T3 Torx Screwdriver](#) (1)
- [Spudger](#) (1)
- [Tweezers](#) (1)

Step 1 — SIM Card



- Insert a fingernail or a spudger into the notch on bottom edge of the phone near the charging port.
- Pry the back cover away from the body of the phone.

Step 2



- Continue to gently lift the back cover until all plastic clips have been released.
 - Remove the back cover.
-  To reinstall the back cover, align the cover over the body and gently press all around the edges until you feel the clips snap into place.

Step 3



- Slide out and remove the SIM card.

Step 4 — Battery



- Remove the nineteen 3.1 mm T3 screws securing the midframe.

Step 5



- Use the point of a spudger to pry up the rubber cover over the camera flash connector.
- Remove the rubber cover.

Step 6




- Use the point of a spudger to pry up and disconnect the camera flash connector.

Step 7



- Loosen the midframe along the edges and lift it away from the body.
- Remove the midframe.


Step 8



⚠ Be very careful not to puncture the battery with any sharp tools. A damaged lithium-ion battery can catch fire and/or explode.

- Peel up and remove the tape securing the battery wires.
 - Peel up and remove the black tape that bridges the battery and the phone.
- ★** While neither tape pieces are necessary for the operation of the phone, save them if they are in good condition for the reinstallation process.

Step 9



- Slip the point of a spudger underneath the red and black battery wires and gently **pry straight up**.
- ⚠ **Do not pull** the plug out, or you will tear the board socket out. Be careful where you pry. Do not pry against the board socket.
- ▣ During reassembly, align the connector in its socket, then press straight down to reconnect it.

Step 10



- Use tweezers or your fingers to de-route the battery wires from the plastic brackets.

Step 11




- Peel the black pull tab from battery and pull slowly but firmly to separate the battery from the frame.
 - A few drops of high concentration (90% or higher) isopropyl alcohol along each side may help soften the adhesive.
 - If the pull tab breaks, use a spudger to gently pry around the edges of the battery until it comes loose.
- ⚠** Don't deform or puncture the battery—it can catch fire and/or explode if damaged.
- ⚠** Never reinstall a damaged or deformed battery. Replace the battery.

Step 12




- Remove the battery.
- ☞ To install a battery, orient the new battery such that the wires exit near the bottom of the phone, and the battery connector is on the motherboard side.
- ☞ Clean off any adhesive residue which may prevent the battery from sitting flush against the frame. Use a few [strips of adhesive included in the battery kit](#) or some [double-sided tape](#) to secure the battery to the frame.

Step 13 — Motherboard



- Using tweezers, lift up the black silicon piece connecting the motherboard to the front casing.
- Using tweezers, remove the red and black cable connecting the motherboard to the front casing.

Step 14




- Using a spudger, remove the two metal pieces connecting the motherboard to the front casing.

Step 15



- Using tweezers, remove the yellow film connecting the rear camera to the motherboard.
- i** The film is connected by an adhesive, so it may take some jostling to remove.

Step 16



- Remove two 4.0 mm T3 Torx screws connecting the motherboard to the front casing.

Step 17



- Using a spudger, lift up and remove the motherboard.

To reassemble your device, follow these instructions in reverse order.