



Nerf N-Strike Maverick O-Ring Replacement

This is a guide for replacing the O-Ring of the Nerf-N-Strike Maverick.

Written By: tanika gorham



INTRODUCTION

This guide shows the steps necessary to replace the O-Ring on the Nerf N-Strike Maverick. First, you should consult steps 1 through 4 of the *Nerf N-Strike Maverick Teardown* guide. Make sure you have a replacement O-Ring on hand.

TOOLS:

- [Phillips #00 Screwdriver](#) (1)
- [Tweezers](#) (1)

PARTS:

- [O-rings](#) (1)
- [Nerf N-Strike Maverick](#) (1)

Step 1 — Nerf N-Strike Maverick Teardown



- The Redeemer. Looks badass with its rotating barrel, but it's going to get a whole lot more badasser quite soon...
- Reminds me of a gun from the Fifth Element.

Step 2



- First thing's first: let's remove some screws. All screws are conveniently Phillips, and all can be removed with a #0 or #00 size screwdriver.
- Remove all ten Phillips screws.

Step 3



- Another Phillips screw hides beneath the cocking mechanism thing. Remove that one as well.
- The cocking mechanism's quite simple. A metal lever pulls back on the air plunger and compresses the large spring. Another small spring returns the slider back into its original position once it's done doing the dirty business..


Step 4



- And just like that, the gun comes apart.
- Visible in the top left corner is the large spring and air plunger.
- I later opened the gun again and put a folded piece of paper in this area. It gave the gun a bit more "punch" when sending darts on their merry way.

This document was generated on 2019-09-23 03:14:53 PM (MST).

Step 5



- Gun tip. I foresee it being black in the future.

Step 6




- First comes out the air plunger. It lifts right up.
- The barrel comes out next.

Step 7




- The trigger is held in place by a sole Phillips screw. It also has a small spring for that authentic handgun "springy" feeling...

Step 8



- The trigger's spring also attaches via a Phillips screw. A couple of twists with the screwdriver and it comes right out.
- The fancy rotator for the barrel is next. I assume that were the gun to break, this would be the part that fails. It's the most complex part of the gun.

Step 9



- Looking down the gun's business end.
- I didn't bother to take the barrel apart. I didn't feel *that* adventurous.


Step 10



- Here it is -- the whole gun taken apart.
- It's so easy to assemble, a child could do it. Maybe Nerf's motto is "From our kids to your kids"?

(i) I sincerely hope Nerf products are manufactured in countries that have strict child labor laws. I in no way, shape, or form condone child labor.

Step 11



- The finished product.
- I took the gun to work and shot these pictures under a better lighting/camera setup... A much better lighting/camera setup.
- For those who like details: [pic1](#) and [pic2](#).

Step 12 — The Beginning



- Follow steps 1 through 4 of the Nerf N-Strike Maverick Teardown guide.

Step 13 — Locate the Gasket



- Locate the air plunger in the upper left hand corner of the opened nerf gun. Push back on the spring and carefully pull the plunger toward you to remove it.

Step 14 — Locating the O-Ring



- Once you have the air plunger removed, locate the O-Ring by pulling the two pieces of the air plunger apart.

Step 15 — Removing the O-Ring



- Use a pair of tweezers to remove the O-Ring from the top of the air plunger.

Step 16



- Follow steps 1 through 4 of the "Nerf N-Strike Maverick Teardown" guide in reverse order to reassemble the gun.

To reassemble your device, follow these instructions in reverse order.