




# Nokia 2115i Screen Replacement

Repairing the replacing the screen

Written By: Shane



## INTRODUCTION

To replace the screen, phone disassembly is required.

### TOOLS:

- Spudger (1)
- T6 Torx Screwdriver (1)

### PARTS:

- Replacement Screen Speaker assembly (1)


## Step 1 — Nokia 2115i Battery



**⚠** To prevent shock, press down on the power button located on the top of the phone until the phone shuts off.

- Press down on the small gray button located on the back of the phone.
- Slide the back plate down and off.

## Step 2



- To remove the battery, begin by holding the phone sideways.
- Then, insert your thumb in the groove below the battery and push the battery up and out.

## Step 3 — Faceplate



- Locate the spudger. A photo of the correct spudger is provided to the left.
- Turn the front of the phone to face you. Find the two small square holes on the bottom left and right sides of the faceplate.
- Insert the spudger into each square hole and push up to detach the face plate.

## Step 4 — Removing the Keypad



- Note: The keypad will be loose and may fall off during this step.
- Pull the face plate up and off of the phone.
- To remove the keypad, simply lift it off the phone.

## Step 5 — Removing the Motherboard




- Locate the 6 screws on the metallic sheet that previously held the keypad. (This sheet, shown in the pictures, is the top side of the motherboard).
  - Note: 2 of the screws are on the bottom corners, 2 are on the right and left edges of the phone below the screen, and 2 are on the very top corners of the phone, above the screen.
  - Warning: The middle two screws are attached to the base of the phone with two black plastic rings. Use tweezers to remove the screws carefully to avoid breaking the plastic rings
  - Use a size T6 Torx screwdriver to remove each of these 6 screws.

## Step 6



- To remove the motherboard, lift it up and off the phone.
- Note: The screen will still be attached to the motherboard.

## Step 7 — Replacing the Screen



- Turn the screen/motherboard so that the screen side is facing down as shown in the first picture of this step.
- With your fingers, push the black tabs on the upper left and upper right sides of the motherboard outward. You can see this in the second picture of this step.

## Step 8



- Turn the motherboard so that the screen faces upward, as seen in the photos.
- Holding the sides of the screen, pull the screen up and off of the motherboard.

***(i)*** Note: When you remove the screen from the motherboard, resistance is normal.

To reassemble your device, follow these instructions in reverse order.