



Opening Procedure

Opening procedure for service or repair of the iPhone X.

Written By: Jeff Suovanen



INTRODUCTION

Prerequisite only guide to open an iPhone X, allowing access to internal components for repair or replacement.

TOOLS:

- [iOpener \(1\)](#)
- [iFixit Opening Picks set of 6 \(1\)](#)
- [Suction Handle \(1\)](#)
- [P2 Pentalobe Screwdriver iPhone \(1\)](#)
- [iSclack \(1\)](#)

Step 1 — Opening Procedure



- ➊ Heating the lower edge of the iPhone will help soften the adhesive securing the display, making it easier to open.
- Use a hairdryer or heat gun or [prepare an iOpener](#) and apply it to the lower edge of the iPhone for about a minute in order to soften up the adhesive underneath.

Step 2



(i) The next two steps demonstrate the iSclack, a handy tool that we recommend for anyone doing frequent repairs. **If you aren't using the iSclack, skip down two steps for an alternate method.**

- If the plastic depth gauge is attached at the center of the iSclack, remove it now—it's not needed for larger phones like the iPhone X.
- Position the suction cups near the bottom edge of the iPhone—one on the front, and one on the back.
- Press both suction cups firmly into place.

(i) If your display or back glass is badly cracked, covering it with a layer of clear packing tape may allow the suction cups to adhere. The iSclack also includes two pieces of tape for this purpose.

Step 3



- Hold onto your iPhone securely and close the handle of the iSclack to slightly separate the screen from the rear case of the phone.
⚠ Don't try to completely separate the screen; a small opening along the bottom edge is all you need.
- Insert an opening pick into the gap.
- **Skip the next two steps.**

Step 4



- If using a single suction handle, apply it to the bottom edge of the phone, while avoiding the curved portion of the glass.
- If your display is badly cracked, covering it with a layer of clear packing tape may allow the suction cup to adhere. Alternatively, very strong tape may be used *instead of* the suction cup. If all else fails, you can superglue the suction cup to the broken screen.

Step 5



- Pull up on the suction cup with firm, constant pressure to create a slight gap between the front panel and rear case.
- Insert an opening pick into the gap.

(i) The watertight adhesive holding the display in place is very strong; creating this initial gap takes a significant amount of force. If you're having a hard time opening a gap, apply more heat, and gently rock the screen up and down to weaken the adhesive until you create enough of a gap to insert your tool.

Step 6



- Slide the opening pick around the lower left corner and up the left edge of the iPhone, slicing through the adhesive holding the display in place.

⚠ Don't insert the opening pick too far into the iPhone, or you may cause damage to internal components.

Step 7



- Re-insert your pick at the bottom edge of the iPhone, and slide it up the right side to continue separating the adhesive.

! Don't insert the pick very far, or you may damage the display cables along this side of the iPhone. Insert it only a few millimeters, or about the width of the display bezel.

Step 8



i The top edge of the display is secured with both glue and clips.

- Slide the opening pick around the top corner of the display, while gently pulling or wiggling the display **down** in the direction of the Lightning port.

! The clips will break if you use too much force. Work carefully and be patient.

! Again, don't insert the pick more than a few millimeters—about the width of the display bezel—or you may damage the front panel sensor array.

- Slide the pick to the opposite corner and cut any remaining adhesive securing the display.

Step 9



- Pull on the small nub on the suction cup to remove it from the front panel.
- If you used an iSlack and it's still affixed to the iPhone, remove it now.

Step 10



- Open the iPhone by swinging the display up from the left side, like the back cover of a book.
- ⚠ Don't try to fully separate the display yet, as several fragile ribbon cables still connect it to the iPhone's logic board.
- Lean the display against something to keep it propped up while you're working on the phone.
- 📌 During reassembly, lay the display in position, align the clips along the top edge, and carefully press the top edge into place before snapping the rest of the display down. If it doesn't click easily into place, check the condition of the clips around the perimeter of the display and make sure they aren't bent.

To reassemble your device, follow these instructions in reverse order.