




# Revlon 473 Thermal Cutout Replacement

The thermal cutout is a safety feature in the hairdryer. If the dryer starts to overheat, the thermal cutout shuts off the device.

Written By: Jessica Leyva



 **TOOLS:**

- Phillips #2 Screwdriver (1)
- Spudger (1)

 **PARTS:**

- Thermal Cutout (1)

## Step 1 — Shell



⚠ Before disassembly, make sure that the device is unplugged.


- Unscrew the two 17.83 mm black screws located on the handle.

## Step 2



- Separate the shell from the main component.
- Make sure that the each piece is free from debris.

## Step 3




- Continue to pull the components apart.
- ⓘ For reassembly, put the silver encasing on before the the black cover.

## Step 4 — Thermal Cutout



- Locate the thermal cutout under the coils of the heating element.

## Step 5



- Test the thermal cutout for continuity using the multimeter.
- **(i)** Make sure the multimeter is set to 200 ACV and bring the probes toward the thermal cutout.
- If the numbers on the multimeter continue to change, the circuit is closed and properly functioning.
- If the multimeter reads a consistent number, the circuit is opened and the thermal cutout needs to be replaced.

## Step 6



- To replace the thermal cutout, use the spudgers to extract the object.
- **(i)** To remove, wedge it back and forth until it comes free.
- You do not need to take out the gold piece, only the thermal cutout.

## Step 7



- Replace the old thermal cutout with a new thermal cutout by snapping it into place.

To reassemble your device, follow these instructions in reverse order.