



Samsung Chromebook 2 XE503c12 Trackpad Replacement

This guide will show you how to replace the trackpad on your Samsung Chromebook 2 XE503c12

Written By: Shane Solomon



This document was generated on 2020-01-11 06:45:51 AM (MST).


INTRODUCTION

This guide will show you step by step how to replace your trackpad for your Samsung Chromebook 2 XE503c12. This guide will also be useful for trackpads that are only slightly malfunctioning, as accessing the trackpad and cleaning it of dust or debris may restore functionality.

TOOLS:

- [Phillips #0 Screwdriver](#) (1)
- [Phillips #00 Screwdriver](#) (1)
- [iFixit Opening Tools](#) (1)
- [Nylon Tipped Tweezers](#) (1)


Step 1 — Trackpad



 Turn the power off before beginning this step.


-  Most Chromebooks contain rubber circle pads on each of the four corners to cover the screws. In order to remove the rubber pads, simply use any opening tool.
- Lay the Chromebook down so that the bottom cover is facing upward.
- Using a Phillips #00 screwdriver, remove all nine 5.5 mm screws from the back cover.

Step 2



- Place the opening tool in the divot between the spine of the Chromebook and the back cover.
- Slowly glide and push down the end of the opening tool along all sides of the Chromebook to detach the brackets. You will hear the brackets detach.



Step 3



- Slowly pry off the back cover of the Chromebook.


⚠ Be gentle while prying to avoid breaking the back cover.

Step 4




- Remove the four 3 mm screws using a Phillips #000 screwdriver.

Step 5



- Carefully lift the top of the battery then pull it away from you to remove it.
- Some batteries may be attached via a battery connector. Disconnect the battery connector by simply pulling straight up at its base.

Step 6




- Using a Phillips #00 screwdriver, remove all of the two screws keeping the trackpad in place.

Step 7




- Gently remove the connector between the trackpad and the motherboard by pulling upward on it at the port.

Step 8




- Using an opening tool, gently peel back the adhesive strip holding the trackpad in place.

Step 9



- Using the opening tool, disconnect the metal trackpad support brackets.
- *(i)* Don't be afraid to use a moderate amount of force when prying the support brackets loose.

Step 10



- With the laptop slightly open, push the trackpad upwards at the rear, and pull it out from the bottom.

To reassemble your device, follow these instructions in reverse order.