



Samsung Galaxy A5 (2017) Back Cover Replacement

This guide shows how to replace the back cover of your Samsung Galaxy A5 2017.

Written By: Dominik Schnabelrauch



INTRODUCTION

Use this guide to replace the back cover of your Samsung Galaxy A5 2017 smartphone.

Opening the Samsung Galaxy A5 will **damage the waterproof sealing** on the device. If you do not replace the adhesive seals, your phone will **function normally**, but will **lose its water-protection**.

If needed, you can use a dropper or syringe to inject isopropyl alcohol (>97%) around the edges of the back cover to weaken the adhesive.

You'll need **replacement adhesive** to reattach the back cover when reassembling the device.

TOOLS:

- [iOpener \(1\)](#)
- [iFixit Opening Picks set of 6 \(1\)](#)
- [Suction Handle \(1\)](#)

Step 1 — Back Cover Removal



- Power off your phone before beginning disassembly.
- Use an [iOpener](#) to loosen the adhesive beneath the back cover. Apply the iOpener for at least two minutes. You might want to repeat this step several times during the back cover removal.

 The adhesive of the Samsung Galaxy A5 (2017) is very strong. A hair dryer, heat gun, or hot plate may also be used if you aren't able to open the device with the iOpener. Be careful not to overheat the phone—the AMOLED display and internal battery are both susceptible to heat damage.

Step 2



- Insert an opening pick at the bottom end of your phone.
- If you can't manage to insert the opening pick between the back cover and the frame, you can use a suction handle to create a small gap.
- Start to slide the tip of the opening pick to the bottom left corner and cut the adhesive with it.
- Leave the opening pick in the bottom left corner to prevent the adhesive from resealing. Insert a new opening pick and start to cut the adhesive on the left side of the phone.

Step 3



- Use an opening pick to cut the adhesive on all sides of the phone. Leave one opening pick in every corner to prevent the adhesive from resealing.
⚠️ [Reuse an iOpener](#) if the adhesive becomes hard to cut. During the removal process the back cover is under tension all the time and is likely to break if the adhesive isn't loose enough.
- Insert an opening pick on the right side of the phone after you cut the adhesive on all sides. Flip it sideways until you can get a good grip on the back cover.

Step 4



- Remove the back cover from the phone.
- **📌** Before applying new adhesive remove any remaining adhesive from the back cover and the frame and clean the areas with isopropyl alcohol and a lint-free cloth.

To reassemble your device, follow these instructions in reverse order. When reassembling your phone apply new adhesive where it is necessary.

Secure the new back cover with pre-cut adhesive or double-sided adhesive tape.

After installing the rear cover, apply strong, steady pressure to your phone for several minutes to **help the adhesive form a good bond**.