



# Samsung Gear VR With Controller Trackpad Replacement

How to remove and replace the trackpad on the left side of the Samsung Gear VR with Controller.

Written By: Jake Criscione



## INTRODUCTION

If the trackpad on your Samsung Gear VR headset is not responding to touch, use this guide to replace the faulty trackpad. For this guide, you will need a Phillips #000 screwdriver, iFixit opening tool, and metal spudger.

### TOOLS:

- [Metal Spudger \(1\)](#)
- [iFixit Opening Tools \(1\)](#)
- [Phillips #000 Screwdriver \(1\)](#)

## Step 1 — Inner Mask



- Push the switch on the right-hand side of the device to separate the cover from the main body.
- Pull the cover away from the main device.

## Step 2



- Remove the four corner screw covers with a metal spudger.

**i** The screw covers fly off when removed, so make sure to keep track of them.

## Step 3



- Use a metal spudger to remove the screw cover centered at the top.

## Step 4



- Remove the six 5mm Phillips #000 screws to detach the front phone mount.
- Lift the front phone mount up and to the left.


**⚠** Remove the front phone mount carefully because there is a wire harness on the left side of the headset.

## Step 5



- Remove the four 5mm Phillips #000 screws that secure the plate on the left side of the headset.
- Pull the plate away from the motherboard gently.

## Step 6



- Use the iFixit opening tool to remove the pop connector holding the wire harness to the motherboard.
- You can now completely remove the front phone mount from the headset.

## Step 7



- Remove the rest of the pop connectors on the motherboard using the iFixit opening tool.
- Pry at the top of the motherboard with the iFixit opening tool to remove the motherboard.

● The largest pop connector may require more effort to remove.

**⚠** Make sure that nothing is connected to the motherboard before you pull it out.

## Step 8



- Remove the eight 5mm Phillips #000 screws on the inner mask.
- Gently separate the inner mask from the headset by pulling the mask from the inner sides of the lens sockets.

## Step 9 — Trackpad



- Remove the one 5mm Phillips #000 screw to detach the trackpad from the headset.
- Pry the trackpad loose from the headset using the spudger.

To reassemble your device, follow these instructions in reverse order.