




Samsung NX2000 LCD Replacement

This is a step by step that will direct you on how to successfully remove the LCD display of your Samsung NX2000. Before taking the camera apart make sure that the battery is out of the camera.

Written By: Maria Zamora



INTRODUCTION

This guide will help you learn how to replace the LCD of Samsung NX2000. It will show you the step by step procedures for removing the display successfully. Be sure to use the correct tool that is safe for the removal and does not damage the device.

TOOLS:

- [Tri-point Y0 Screwdriver](#) (1)
- [Spudger](#) (1)
- [Metal Spudger](#) (1)

Step 1 — LCD



- First begin by flipping your camera upside down.
- Remove the seven 4mm screws from indicated circles shown using a Y0 screwdriver. There are three on the bottom, and two on each side

! Remember to store the screws in a secure place.


Step 2



- Insert a plastic opening tool into the gap between the camera body and the back panel. Carefully pry open the camera and separate the back panel.


! When working with electronics, it's important to choose a tool that's ESD-safe to avoid accidental damage to the device. The metal spudger is great when you need serious prying power, but the regular black nylon spudger or a plastic opening tool should be used whenever possible.

Step 3




- Before taking it apart you'll have to detach the display ribbon cable.
- Use a plastic opening tool, lift up the black strip to release the ribbon cable from the connector.

Step 4




- Separate the LCD half compartment of the camera from the main body.

Step 5




- Remove the four 1mm screws with the Y0 screwdriver.

Step 6



- Use a plastic opening tool or tweezers to lift the green tape located on top of the LCD controller board.
- Detach the two ribbon cables, by first lifting the black tab on top of the connector.
- Pull the ribbon cables out of the connectors with tweezers or two fingers.

Step 7



- Place blue plastic spudger in between LCD screen and plastic surrounding.
- Begin to lift up slowly, removing the LCD screen from the main frame.

Step 8



- The LCD screen is now separated from the main frame.

To reassemble your device, follow these instructions in reverse order.