



Sew-on Patch

Patch jeans with a sew-on patch.

Written By: Brittany McCrigler



INTRODUCTION

Patch jeans with a sew-on patch. This technique is also applicable for adding patches to bags, bandanas, and boy-scout uniforms. Patches can also be sewn on by hand.

For replacement parts or further assistance, contact [Patagonia Customer Service](#).

TOOLS:

- [Sewing Machine](#) (1)
 - [Utility Scissors](#) (1)
 - [Sewing Pins](#) (1)
-

Step 1 — Sew-on Patch



- Examine the damage. Clip any loose threads and remove any debris from the tear.
- Grab a trendy patch.

Step 2



- Position the patch over the hole.
- Any patch you use should overlap the damage by at least 1/8".

Step 3



- Pin the patch to the jeans.

⚠ Be sure to only pin the patch to one layer of denim, or you will sew the pants shut.

Step 4



- Slide the jeans into the sewing machine, positioning the needle over the edge of the patch.

⚠ Be sure you only have one layer of the jeans between the needle and the sewing machine arm, or you will sew the pants shut.

Step 5



- Lower the pressor foot.
 - Sew along the edge of the patch.
 - Remove the pins before you get to them.
- ⚠ Sewing over a pin can bend or break the needle.

Step 6



- Continue sewing around the patch, lifting the pressor foot to turn at corners of the patch.

Step 7



- When you come all the way around, overlap the first two or three stitches.
- Lift the needle and pressor foot.
- Slide the jeans out of the sewing machine.
- Clip any threads, and admire your work.