



Sony Xperia L2 LTE Screen Replacement

Use this guide to replace your broken phone screen for your Sony Xperia L2 LTE.

Written By: Carrie Schmitt



INTRODUCTION

This guide will take you step by step through the process of replacing your Sony Xperia L2 screen. This guide will help those who have a broken or unresponsive screen to extend the life of your phone.

TOOLS:

- [T4 Torx Screwdriver](#) (1)
- [iFixit Opening Tools](#) (1)
- [iOpener Kit](#) (1)

Step 1 — Battery



⚠ Before disassembling the battery, power off your Sony Xperia L2 LTE.


- Remove SIM card tray.

Step 2





- Use the plastic opening tool to pry the back case of the phone off.
- ⚠ The fingerprint sensor is connected to the motherboard.
- Disconnect the fingerprint sensor.

Step 3



- Unscrew all 10 screws from the top and bottom portion of the phone using a T4 Torx screwdriver.
- Use the plastic opening tool to remove the unscrewed top and bottom portion of the phone.

Step 4




- Disconnect the battery cable from the motherboard.
- Pry up the battery and remove it from the device.

(i) Battery may have adhesive that needs to be removed prior to removing the battery.


⚠ Be careful not to jab the battery with any sharp tools. A punctured battery may leak dangerous chemicals or catch fire.

Step 5 — Motherboard



- Unclip circuit connectors from phone to motherboard.

Step 6



- Use blue plastic opening tool to pry off the motherboard.

Step 7 — Screen



- Microwave the iOpener for 30 seconds.
- Place the iOpener on the phone screen for 90 seconds to loosen the adhesive.
- Use the suction tool and a pick to remove the screen from the phone.

⚠ The iOpener will be very hot, so be careful when handling it. Use an oven mitt if necessary.

Step 8



- Unhook the screen sensor from the phone to detach the screen from the device.

To reassemble your device, follow these instructions in reverse order.