



Toilet Paper Holder Replacement

Replace your toilet paper holder.

Written By: Elizabeth Opheim



INTRODUCTION

Over time, the screws and brackets securing a toilet paper holder can loosen or become disconnected entirely. This guide will walk you through the steps of replacing a broken or loose toilet paper holder.

TOOLS:

- [Screwdriver \(1\)](#)
- [Phillips #0 Screwdriver \(1\)](#)
- [Tape Measure \(1\)](#)

PARTS:

- [Safety Glasses \(1\)](#)
- [Marker \(1\)](#)

Step 1 — Toilet Paper Holder



- Unscrew the four screws of the original broken holder.
- You may want to wear gloves.
- If there is damage to the wall behind the old holder, check out the iFixit guide for [repairing a hole in drywall](#).

Step 2



- Measuring the area where you want your new holder to go, mark two lines 6.8" apart.
- Measure an inch and a third (1 and 1/3") above the marks and mark these new spots where your screws will go.
- While marking where you want to place the new holder, use a leveling tool to make sure that the toilet paper will be sitting flat.

Step 3



- Place the new screw inside the new bracket and line up the mark with the base of the screw.
- Make sure that the indentation for the toilet paper holder is facing in.
- Repeat this for the top and bottom screws on both the left and right bracket bases (4 times total).

Step 4



- Insert the spring loaded toilet roll bar and enjoy.

Hopefully you have enjoyed exploring this repair guide and now understand how to repair and replace a broken toilet paper roll holder.