



Toshiba Satellite C655D-S5084 Random Access Memory (RAM) Replacement

Installing Random Access Memory (RAM) in Toshiba Satellite C655D-S5084.

Written By: Shelby Kunz



INTRODUCTION

Is your computer running slow? Just need some more space? In this installation guide we are going to take you through the steps to install Random Access Memory (RAM) in your Toshiba Satellite C655D-S5084.

TOOLS:

- Phillips #1 Screwdriver (1)

PARTS:

- [PC3-10600 2 GB RAM Chip \(1\)](#)
- [PC3-10600 4 GB RAM Chip \(1\)](#)

Step 1 — Random Access Memory (RAM)



- Turn the laptop over and place upside down on a flat surface.
- Remove the 5.5 mm "F5" screw with the Phillips #1 screwdriver and lift off plastic cover.

Step 2



- Take two fingers and gently pull the two metal tabs away from the RAM module as shown.
 - There are two tabs for each of the two RAM modules.
 - The RAM module should be slightly dislodged from the base after the two tabs are pulled.

Step 3



- Grip the edge of the card and slide the RAM module out by pulling horizontally.

i Once the first RAM module has been removed, repeat steps 2 and 3 to remove the second RAM module.

To reassemble your device, follow these instructions in reverse order.