



Video Guide Rancilio Silvia Grouphead Screen And Gasket Replacement Grouphead Gasket & Screen Replacement

Learn how to remove the clogged old screen, deep clean grouphead and install new screen and gasket.

Written By: Samuel Kanenwisher



INTRODUCTION

Learn how to remove the clogged old screen, deep clean grouphead and install new screen and gasket.

TOOLS:

- Craftsman 5/16" x 1 3/4" slotted screwdriver (1)
- Wire Brush (1)
- Canned Air (1)
- 3/16" Punch (1)
- Hook & Pick Set (1)

PARTS:

- Coffee Detergent (We like Joe Glo) (1)
- Rancilio Silvia Grouphead Gasket and Screen (1)

Step 1 — Identify Version & Prepare Machine For Tune-Up



- Identification instructions.

Step 2 — Remove Water Tank



- Remove water tank, hoses, and tuck them back in the machine.

Step 3 — Flip Machine



- Remove drip tray. Flip the machine upside down.

Step 4 — Remove The Screen & Diffuser



- Remove screen screw with flat head screwdriver.

Step 5 — Remove the old screen.



- Remove old screen and diffuser.

Step 6 — Remove and soak diffuser.



- Remove and soak diffuser in Joe Glo coffee cleaner.

(i) On version 3 you will need to remove and soak the brass disc as well.

Step 7 — Remove Old Grouphead Gasket



- Pry the gasket up with the sharp tip of the awl.

Step 8 — Don't Stab Yourself!



- Carefully remove old gasket.

Step 9 — Soak grouphead.



- Use Joe Glo coffee cleaner and hot water to soak the grouphead for 10-15 minutes.

Step 10 — Cleaning Grouphead



- A dental pick works great for cleaning the grouphead.

Step 11 — Clean with flathead screwdriver.



- Use a small flathead to clean the bottom surface of the grouphead.

Step 12 — Clean with wire brush.



- A small stainless steel brush works well. They can be found at your local hardware store.

Step 13 — Remove water with towel.



- Use a paper towel / regular towel to soak the dirty water from the grouphead.

Step 14 — Blow out rest of water.



- Use the compressed air can to clean any excess water or coffee.

Step 15 — Final scraping.



- Last but not least, use the pick on the top and bottom rails to remove last bits of coffee debris.

Step 16 — Install New Gasket & Screen



- Remove parts from bag.

Step 17 — Insert gasket with lettering down.



- Take the new gasket and install it with the lettering down.
- Use a 1/4 inch flat punch to push down the gasket to ensure its nice and flat.

Step 18 — Install diffuser and screw.



- Insert the diffuser with the water channels facing down.

Step 19 — Install 8mm screw.



- Use an 8mm socket wrench to tighten the screw.

Step 20 — Tighten screw.



- Careful not to over tighten and break screw. It will be extremely difficult to remove.

To reassemble your device, follow these instructions in reverse order.