



Xbox One Stereo Headset Microphone Replacement

This guide will show you how to replace a broken microphone in your Xbox One Stereo Headset.

Written By: Trevor Steele



INTRODUCTION

This guide has only a few simple steps to get to the microphone. However, soldering is required to fully detach the microphone from the headset and install a replacement. Please refer to the [soldering technique guide](#) for instructions on soldering and desoldering.

TOOLS:

- Spudger (1)
- Metal Spudger (1)
- Flathead 3/32" or 2.5 mm Screwdriver (1)
- Soldering Workstation (1)

Step 1 — Microphone



- Use the flat end of a spudger to pry out the rubber stopper at the base of the boom.

Step 2



- Remove the single 6 mm flathead #2.0 screw exposed after removing the rubber stopper.

Step 3



- Lift the joint of the boom up and over its pivot point to separate the microphone from the headset.

Step 4



- Using the flat end of the metal spudger, pry the back plate off the boom.

(i) The back plate is glued to the boom and must be removed gently.

 When re-installing, apply a few drops of super glue to hold it in place.

Step 5



- Pull the back plate off the boom.

Step 6



- Using the flat end of the plastic spudger, gently pry the microphone out of its casing.
- Desolder the two wires from the back of the microphone. For instructions on how to solder and desolder, please see the [soldering technique guide](#).

 The white wire connects to the positive node, which is indicated with a "+" on the microphone.

To reassemble your device, follow these instructions in reverse order.