



# ZTE ZMAX Z970 Screen Replacement

Removing the screen for the ZTE ZMAX Z970 and replacing it.

Written By: Ismail Jhaveri



## INTRODUCTION

How to remove the screen for the ZTE ZMAX Z970. Removing the screen is easiest with an iOpener which requires a microwave.

### TOOLS:

- [Tweezers \(1\)](#)
- [Spudger \(1\)](#)
- [Phillips PH000 Screwdriver \(1\)](#)
- [iFixit Opening Tools \(1\)](#)
- [iOpener \(1\)](#)
- [iFixit Opening Picks set of 6 \(1\)](#)

## Step 1 — Battery



- Insert a fine point tool into the hole on the top left side of the phone to remove the SIM and SD card trays.
- Pull out the trays.

## Step 2




- Insert a plastic opening tool into the groove between the phone's back cover and casing.
- Move the plastic opening tool along the edges of the phone to unclip the two pieces.

## Step 3



- Remove the ten 1.2mm screws with a Phillips #000 screwdriver.

## Step 4




- Remove the mid frame with the plastic opening tool.

## Step 5



- Disconnect the battery from the motherboard.

## Step 6



- Wedge a spudger underneath the battery and gently pry upwards to remove the battery.
- Once free from the glue, remove from device.

 The glue holding down the battery is strong so work slow and cautiously to avoid starting a fire.

## Step 7 — Screen



- Heat up the iOpener for 30 seconds and place on top of the phone for 2 minutes.

## Step 8



- Wedge the opening picks into all the corners of the phone and lift until the screen comes off.

To reassemble your device, follow these instructions in reverse order.