




# iMac G3 Model M4984 Power Supply Replacement

Written By: Chris Green



## INTRODUCTION

The iMac uses an incredibly hard to get to power supply. It has 24-Pins. This will require taking the iMac fully apart.


### TOOLS:

- Flathead Screwdriver (1)
- Phillips #0 Screwdriver (1)
- Phillips #00 Screwdriver (1)

### PARTS:

- 661-2081 (Rev 1) 661-2167 (Rev 2) (1)

## Step 1 — Logic Board



- The iMac G3. This was a great computer for the time, and had plenty of features.

## Step 2



- Start by flipping the iMac upside-down. It may help to lay it on a towel, so you don't damage the screen, or scratch the face.

## Step 3



- Remove this Phillips screw.
- Using a flathead screwdriver, work your way around the bottom cover, until it comes off.
- Then, lift the bottom cover up and out, and set it aside.

## Step 4



- Now, remove the DB-15 Video connector from the logic board.
- It may be helpful to use a Phillips screwdriver to remove the thumbscrews.

## Step 5




- Remove the power cable from the logic board assembly.

## Step 6




- Remove the front panel connector.

## Step 7




- Now, remove these Phillips screws.
- Now, grab the logic board assembly by the piece of plastic, and lift it out.

## Step 8




- The logic board assembly. This is the heart of the computer, it contains the motherboard, CPU, RAM, V-RAM, PRAM battery, the hard drive, and the optical drive.

## Step 9 — Power Supply



- Now, remove these screws.
- Now, lift the bottom cover off.

## Step 10




- Removing the front bezel:
- There isn't a great position to put the iMac in to remove the front bezel. I recommend flipping it so it like it would normally be positioned.
- Remove these two Phillips screws.
- Now, work your way around the bezel with a flathead screwdriver, and then, pivot it up towards the top, and remove it.

## Step 11




- Removing the translucent plastic:
- Removal of the front bezel will reveal two screw covers on the top, pop them off with a Phillips screwdriver.
- Now, use a Phillips screwdriver to remove the screws.
- You can now remove the plastic.

## Step 12



- Removing the EMI Shield:
- Remove all 10 of these screws, and lift the EMI Shield off.



## Step 13



- Power Supply:
- Removal of the EMI shield will reveal two major circuit boards.
- The Display Driver:
- The Power Supply:


**⚠** The power supply and driver board are dangerous, if you do not know what you are doing, you could severely injure or kill yourself.

## Step 14



- Remove these three screws.

## Step 15



- Now, swing the board out, and remove the following connectors:
  - AC Power
  - To System Fan
  - Don't remove this. It comes free with the logic board power.
  - To Display Driver
- The connector that is attached to the logic board; to remove it, simply thread it through the hole in the metal:
- Now, you should be able to remove the power supply.

To reassemble your device, follow these instructions in reverse order.