



# iPhone 5 Lightning Connector and Headphone Jack Replacement

Remove the Lightning connector, headphone jack, and cellular antenna from your iPhone 5.

Written By: Arthur Shi



## INTRODUCTION

The Lightning connector, headphone jack, and cellular antenna are on a single assembly and must be removed and replaced together.

You can also use this guide to replace the [microphone gasket](#).

[video: <https://www.youtube.com/watch?v=wfD4VqC5OKI>]

### TOOLS:

- [Phillips #000 Screwdriver \(1\)](#)
- [iFixit Opening Tools \(1\)](#)
- [Suction Handle \(1\)](#)
- [Spudger \(1\)](#)
- [P2 Pentalobe Screwdriver iPhone \(1\)](#)
- [iOpener \(1\)](#)
- [Standoff Screwdriver for iPhones \(1\)](#)

### PARTS:

- [iPhone 5 Lightning Connector and Headphone Jack \(1\)](#)
- [iPhone 5 Dock Connector Cable Bracket \(1\)](#)
- [iPhone 5 Microphone Gasket \(1\)](#)

## Step 1 — Taping the display glass



- If your display glass is cracked, keep further breakage contained and prevent bodily harm during your repair by taping the glass.
- Lay overlapping strips of clear packing tape over the iPhone's display until the whole face is covered.
- *(i)* This will keep glass shards contained and provide structural integrity when prying and lifting the display.

 Wear safety glasses to protect your eyes from any glass shaken free during the repair.

## Step 2 — Remove the Pentalobe screws



 Before you proceed, discharge your iPhone battery below 25%. A charged lithium-ion battery can catch fire and/or explode if accidentally punctured.

- Power off your iPhone before beginning disassembly.
- Remove the two 3.6 mm Pentalobe screws next to the Lightning connector.

## Step 3 — How to prevent display separation



- ⓘ In the following steps you will be pulling the display up out of the phone body. The display is composed of a glass screen and a plastic bezel with metal clips.
  - Regardless of the tool you use, you need to be sure you pull up the entire display.
  - If the glass begins to separate from the plastic, as shown in the first image, slide a plastic opening tool between the plastic frame and the metal phone body to pry the metal clips out of the case.
- ⚡ If you are reassembling a phone with a separated display bezel, you may want to place a thin strip of adhesive between the plastic bezel and the glass to keep the phone closed.

## Step 4 — Starting the iSclack Opening Procedure



- ⓘ The next two steps demonstrate using the [iSclack](#), a great tool for safely opening the iPhone 5 that we recommend for anyone doing more than one repair. **If you aren't using the iSclack, skip to [Step 6](#).**
- Close the handle on the iSclack, opening the suction-cup jaws.
  - Place the bottom of your iPhone in between the suction cups, against the plastic depth gauge.
    - The top suction cup should rest just above the home button.
  - Open the handles to close the jaws of the iSclack. Center the suction cups and press them firmly onto the top and bottom of the iPhone.

## Step 5 — Finishing the iSclack Opening Procedure



- Hold onto your iPhone securely and close the handle of the iSclack to separate the suction cups, pulling the front panel up from the rear case.
- The iSclack is designed to safely open your iPhone just enough to separate the pieces, but not enough to damage any cables.
- Peel the two suction cups off your iPhone.
- **Skip the next three steps and continue on [Step 9](#).**

## Step 6 — Manual Opening Procedure



- Press a suction cup onto the screen, just above the home button.
- *i* Be sure the cup is completely on the screen to get a tight seal.
- *i* If you're opening an iPhone with cracked glass, neatly lay a couple strips of packing tape across the front and squeeze out as many bubbles as you can. This will give the suction cup a surface to grab, and minimize the spread of broken glass.

## Step 7 — Start lifting the front panel assembly



- ❶ Make sure the suction cup is firmly attached to the front panel assembly.
- While holding the iPhone down with one hand, pull up on the suction cup to slightly separate the front panel assembly from the rear case.
- ❷ Take your time and apply firm, constant force. The screen is a much tighter fit than most devices.
- With a plastic opening tool, begin to gently pry the rear case down, away from the screen, while you pull up with the suction cup.
- ❸ There are several clips attaching the front panel assembly to the rear case, so you may need to use a combination of the suction cup and plastic opening tool to free the front panel assembly.

## Step 8 — Detaching the front panel side clips



- Continue to pry up around the sides of the front panel assembly, detaching the clips along the left and right side.

## Step 9 — Opening up the phone



! Do not try to completely remove the front panel assembly from the rear case, as there are several ribbon cables still attached at the top of the iPhone.

- Once the clips have been released on the bottom and sides of the front panel assembly, pull the bottom of the assembly away from the rear case.
- Open the display to about a 90° angle, and lean it against something to keep it propped up while you're working on the phone.
- Add a rubber band to keep the display securely in place while you work. This prevents undue strain on the display cables.

## Step 10 — Removing the battery connector bracket screws




- Remove the following two screws securing the metal battery connector bracket to the logic board:
  - One 1.8 mm Phillips screw
  - One 1.6 mm Phillips screw

## Step 11 — Removing the battery connector bracket



- Remove the metal battery connector bracket from the iPhone.

## Step 12 — Disconnecting the battery connector




- Use a plastic opening tool to gently pry the battery connector up from its socket on the logic board.

**⚠** Be careful not to dislodge the small surface-mounted components surrounding the socket.

**⚠** Be very careful to only pry up on the battery connector itself and **not** the socket on the logic board. If you pry up on the logic board socket or the board itself, you may destroy the socket or damage nearby components on the board.

## Step 13 — Removing the front panel assembly cable bracket screws



- Remove the following screws securing the front panel assembly cable bracket to the logic board:

- Two 1.2 mm Phillips screws

- One 1.6 mm Phillips screw


**i** This screw tends to not be attracted to a magnetized screwdriver. Take care not to lose it when removing, and make sure it gets back into the right place—a magnetized screw may interfere with the compass.

## Step 14 — Removing the front panel assembly cable bracket



- Lift the display cable bracket toward the battery to unhook it, and remove it from the iPhone.
- ☒ During reassembly, clip the left-hand hooks under the logic board and lower the bracket towards the outside of the phone.

## Step 15 — Disconnecting the front panel assembly cables



**⚠** Make sure the battery is disconnected before you disconnect or reconnect the cables in this step.

- Use a plastic opening tool or a fingernail to disconnect the three front panel assembly cables:
  - Front-facing camera and sensor cable
  - LCD cable
  - Digitizer cable

**⚠** When reassembling your phone, the LCD cable may pop off the connector. This can cause white lines, or nothing at all to appear when powering your phone back on. If that happens, simply reconnect the cable and power cycle your phone. The best way to power cycle your phone is to [disconnect and reconnect the battery](#).

## Step 16 — Separating front panel assembly and rear case



- Remove the front panel assembly from the rear case.

## Step 17 — Speaker Enclosure



- Use the point of a spudger to pry up and disconnect the antenna cable from the logic board.

## Step 18



- Remove the following screws securing the speaker enclosure to the rear case:
    - One 2.5 mm Phillips screw
    - One 1.5 mm Phillips screw
    - One 2.5 mm Phillips screw
    - One 2.7 mm standoff screw
- (i)*** Standoff screws are best removed using an [iPhone Standoff Screwdriver Bit](#) and [driver handle](#).

**!** In a pinch, a small flathead screwdriver will do the job—but use extra caution to ensure it doesn't slip and damage surrounding components.

## Step 19



- Slide the point of a spudger underneath the spring contact flex cable below the battery and gently loosen it from the speaker enclosure.


## Step 20



- Use the flat end of a spudger to pry up and loosen the speaker enclosure from the rear case.
- Pull the speaker enclosure out of its recess.


 During reinstallation, be sure to slide the speaker enclosure underneath this metal washer.

## Step 21




- Remove the small double-sided metal washer on the speaker enclosure and transfer it to the replacement part.

## Step 22 — Lightning Connector and Headphone Jack



- Remove the following screws securing the Lightning connector assembly to the rear case:
    - One 2.9 mm Phillips screw
    - One 1.5 mm Phillips screw
    - Two 3.3 mm Phillips screws
- During re-installation, make sure that the headphone jack's plastic protrusion lies above the metal washer.

## Step 23



- Use the opening tool to pry up and disconnect the Lightning connector cable connector from its socket on the logic board.

## Step 24




- Flip the phone face up, [heat an iOpener](#), and apply it to the right edge of the phone for a minute.

## Step 25





- Slide an opening pick underneath the Lightning connector flex cable to loosen it from the logic board and the rear case.

## Step 26




- Use the flat end of a spudger to loosen the rest of the Lightning connector assembly from the rear case.

## Step 27



- Angle the Lightning connector assembly and pull it out of its recess.
  - Remove the four metal washers and set them aside for reassembly.
-  Before reassembly, use the opening tool or the flat end of a spudger to remove all adhesive residue from the rear case. You can use high-concentration isopropyl alcohol to help with the stubborn spots.

## Step 28



- Use tweezers to gently pull and remove the rubber microphone sleeve off of the microphone. Transfer the sleeve onto the replacement part.

Compare your new replacement part to the original part. You may need to transfer remaining components or remove adhesive backings from the new part before installing.

To reassemble your device, follow these instructions in reverse order.

Take your e-waste to an [R2 or e-Stewards certified recycler](#).

Repair didn't go as planned? Check out our [iPhone 5 Answers community](#) for troubleshooting help.