




iPod shuffle 3rd Generation Front Case Replacement

Front case replacement.

Written By: Matthew Newsom



INTRODUCTION


Replace a scratched front case to make your iPod Shuffle like new.



TOOLS:

- [Metal Spudger](#) (1)
 - [Phillips #000 Screwdriver](#) (1)
 - [iFixit Opening Tools](#) (1)
 - [Spudger](#) (1)
-

Step 1 — Rear Case



- Widen the small gap between the front and rear case by inserting a metal spudger into the gap near the top of the iPod.

 Be careful when using a metal spudger, as you may scratch the outer case.

Step 2



- Insert an iPod opening tool into the newly widened gap, and pry the rear case up and away from the front case.

Step 3




- Insert the iPod Shuffle opening tool into the gap between the front and rear case on the same side, at the bottom corner of the iPod.
- Pry the rear case away from the front case.

Step 4



- Lift the bottom of the rear case and remove it from the rest of the iPod.

Step 5 — Logic Board




- Disconnect the headphone jack and shuffle switch connector by prying it off the logic board with a spudger.

Step 6




- Remove the single Phillips screw securing the logic board to the front case.

Step 7




- Peel the battery up from the front case with an iPod opening tool.
- Remove the logic board and battery from the iPod.

Step 8 — Headphone Jack & Shuffle Switch




- Pry the headphone jack from the front case with an iPod opening tool.
- ⚠ Don't attempt to remove the headphone jack yet, it is connected to the shuffle switch.

Step 9



- Using the pointed tip of a spudger, push the shuffle switch in to separate it from the front case.

Step 10



- Remove the headphone jack and shuffle switch from the front case.

To reassemble your device, follow these instructions in reverse order.